




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Lines should not be too long

Code Smell

JEE applications should not "getClassLoader"

Bug

Math should not be performed on floats

Bug

"equals" methods should be symmetric and work for subclasses

Bug

Literal suffixes should be upper case

Code Smell

Unicode-aware versions of character classes should be preferred

Code Smell

Use Java 12 "switch" expression

Code Smell

"serialVersionUID" should not be declared blindly

Code Smell

"Stream.collect()" calls should not be redundant

Code Smell

Local constants should follow naming conventions for constants

Code Smell

Unit tests should throw exceptions

Code Smell

Test methods should comply with a naming convention

Code Smell

Primitives should not be boxed just for "String" conversion

Analyze your code

Code Smell

Major ?

performance

"Boxing" is the process of putting a primitive value into a primitive-wrapper object. When that's done purely to use the wrapper class' toString method, it's a waste of memory and cycles because those methods are static, and can therefore be used without a class instance. Similarly, using the static method valueOf in the primitive-wrapper classes with a non-String argument should be avoided.

Noncompliant Code Example

```
int myInt = 4;
String myIntString = (new Integer(myInt)).toString(); // Non
myIntString = Integer.valueOf(myInt).toString(); // Noncompl
```

Compliant Solution

```
int myInt = 4;
String myIntString = Integer.toString(myInt);
```

Available In:

sonarlint





sonarcloud

sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-2131

1/2

<div>Value-based objects should not be serialized</div> <div> Code Smell</div>
<div>Default annotation parameter values should not be passed as arguments</div> <div> Code Smell</div>
<div>Method parameters should be declared with base types</div> <div> Code Smell</div>
<div>Fields should not be initialized to default values</div> <div> Code Smell</div>