




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules 632

Vulnerability 53

Bug 154


Security Hotspot 36

Code Smell 389


Quick Fix 42


Tags ▾


Search by name... 🔍


 Vulnerability


Reflection should not be vulnerable to injection attacks





 Authorizations should be based on strong decisions





 OpenSAML2 should be configured to prevent authentication bypass





 Server-side requests should not be vulnerable to forging attacks




 Collections should not be modified while they are iterated



 Equals method should be overridden in records containing array fields



 Reflection should not be used to increase accessibility of records' fields

 AssertJ assertions with "Consumer" arguments should contain assertion inside consumers




 The regex escape sequence \cX should only be used with characters in the @-_ range

 Regular expressions should not overflow the stack

 Tests method should not be annotated with competing

"Random" objects should be reused

Analyze your code

 Bug  Critical  owasp

Creating a new Random object each time a random value is needed is inefficient and may produce numbers which are not random depending on the JDK. For better efficiency and randomness, create a single Random, then store, and reuse it.

The Random () constructor tries to set the seed with a distinct value every time. However there is no guarantee that the seed will be random or even uniformly distributed. Some JDK will use the current time as seed, which makes the generated numbers not random at all.

This rule finds cases where a new Random is created each time a method is invoked.

Noncompliant Code Example

```
public void doSomethingCommon() {
    Random rand = new Random(); // Noncompliant; new instance
    int rValue = rand.nextInt();
    //...
```

Compliant Solution

```
private Random rand = SecureRandom.getInstanceStrong(); //

public void doSomethingCommon() {
    int rValue = this.rand.nextInt();
    //...
```




Exceptions

A class which uses a Random in its constructor or in a static main function and nowhere else will be ignored by this rule.

See

- [OWASP Top 10 2017 Category A6](#) - Security Misconfiguration





Available In:

 |  | 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-2119

1/2

annotations  Bug
Assertions should not be used in production code  Bug
DateTimeFormatters should not use mismatched year and week numbers  Bug
Unicode Grapheme Clusters should be avoided inside regex character classes  Bug