

Secrets

ABAP

Apex

C

C++

CloudFormation

COBOL

C#

CSS

Flex

Go

HTML

Java

JavaScript

Kotlin

Objective C

PHP

PL/I

PL/SQL

Python

RPG

Ruby

Scala

Swift

Terraform

Text

TypeScript

T-SQL

VB.NET

VB6

XML

Java

Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags

Search by name...

Wildcard imports should not be used

Code Smell

Modulus results should not be checked for direct equality

Code Smell

Comparators should be "Serializable"

Code Smell

"Serializable" classes should have a "serialVersionUID"

Code Smell

"switch" statements and expressions should not be nested

Code Smell

Constructors should only call non-overridable methods

Code Smell

Methods should not be too complex

Code Smell

Control flow statements "if", "for", "while", "switch" and "try" should not be nested too deeply

Code Smell

"if ... else if" constructs should end with "else" clauses

Code Smell

Control structures should use curly braces

Code Smell

Expressions should not be too complex

Code Smell

Mockito argument matchers should be used on all parameters

Bug

"Integer.toHexString" should not be used to build hexadecimal strings

Analyze your code

Code Smell

Major

cwe

Using `Integer.toHexString` is a common mistake when converting sequences of bytes into hexadecimal string representations. The problem is that the method trims leading zeroes, which can lead to wrong conversions. For instance a two bytes value of 0x4508 would be converted into 45 and 8 which once concatenated would give 0x458.

This is particularly damaging when converting hash-codes and could lead to a security vulnerability.

This rule raises an issue when `Integer.toHexString` is used in any kind of string concatenations.

Noncompliant Code Example

```
MessageDigest md = MessageDigest.getInstance("SHA-256");
byte[] bytes = md.digest(password.getBytes("UTF-8"));

StringBuilder sb = new StringBuilder();
for (byte b : bytes) {
    sb.append(Integer.toHexString(b & 0xFF)); // Noncompliant
}
```

Compliant Solution

```
MessageDigest md = MessageDigest.getInstance("SHA-256");
byte[] bytes = md.digest(password.getBytes("UTF-8"));

StringBuilder sb = new StringBuilder();
for (byte b : bytes) {
    sb.append(String.format("%02X", b));
}
```

See

- MITRE, [CWE-704](#) - Incorrect Type Conversion or Cast
- Derived from FindSecBugs rule [BAD_HEXA_CONVERSION](#)

Available In:

sonarlint

sonarcloud



sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-4425

1/2

 Bug
<div>Spring "@Controller" classes should not use "@Scope"</div> <div> Bug</div>
<div>Constructor injection should be used instead of field injection</div> <div> Bug</div>
<div>Classes that don't define "hashCode()" should not be used in hashes</div> <div> Bug</div>
<div>Floating point numbers should not be tested for equality</div> <div> Bug</div>