




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6


 XML





## Java static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code


All rules **632**

 Vulnerability **53**


 Bug **154**

 Security Hotspot **36**


 Code Smell **389**

 Quick Fix **42**

Tags ▾


Search by name... 

Exceptions should not be created without being thrown




Bug

Collection sizes and array length comparisons should make sense




Bug

Consumed Stream pipelines should not be reused




Bug

Intermediate Stream methods should not be left unused




Bug

All branches in a conditional structure should not have exactly the same implementation




Bug

Optional value should only be accessed after calling isPresent()




Bug

Overrides should match their parent class methods in synchronization




Bug

Value-based classes should not be used for locking




Bug

Expressions used in "assert" should not produce side effects




Bug

"volatile" variables should not be used with compound operators




Bug

"getClass" should not be used for synchronization



Bug




Min and max used in combination



Bug

Setting JavaBean properties is security-sensitive

Analyze your code

 Security Hotspot  Critical  cwe owasp cert

Setting JavaBean properties is security sensitive. Doing it with untrusted values has led in the past to the following vulnerability:

- [CVE-2014-0114](#)

JavaBeans can have their properties or nested properties set by population functions. An attacker can leverage this feature to push into the JavaBean malicious data that can compromise the software integrity. A typical attack will try to manipulate the ClassLoader and finally execute malicious code.

This rule raises an issue when:

- BeanUtils.populate(...) or BeanUtilsBean.populate(...) from [Apache Commons BeanUtils](#) are called
- BeanUtils.setProperty(...) or BeanUtilsBean.setProperty(...) from [Apache Commons BeanUtils](#) are called
- org.springframework.beans.BeanWrapper.setPropertyValue(...) or org.springframework.beans.BeanWrapper.setPropertyValues(...) from Spring is called

**Ask Yourself Whether**

- the new property values might have been tampered with or provided by an untrusted source.
- sensitive properties can be modified, for example: `class.classLoader`

There is a risk if you answered yes to any of those questions.

**Recommended Secure Coding Practices**

Sanitize all values used as JavaBean properties.

Don't set any sensitive properties. Keep full control over which properties are set. If the property names are provided by an untrusted source, filter them with a whitelist.

**Sensitive Code Example**







```
Company bean = new Company();
HashMap map = new HashMap();
Enumeration names = request.getParameterNames();
while (names.hasMoreElements()) {
    String name = (String) names.nextElement();
    map.put(name, request.getParameterValues(name));
}
BeanUtils.populate(bean, map); // Sensitive: "map" is popula
```

**See**

- [OWASP Top 10 2021 Category A3](#) - Injection
- [OWASP Top 10 2021 Category A8](#) - Software and Data Integrity Failures
- [OWASP Top 10 2017 Category A1](#) - Injection

https://rules.sonarsource.com/java/RSPEC-4512

1/2

<div>min and max used in combination should not always return the same value</div> <div> Bug</div>	<div><ul style="list-style-type: none"><li>• <a href="#">MITRE, CWE-915</a> - Improperly Controlled Modification of Dynamically-Determined Object Attributes</li><li>• <a href="#">CERT, MSC61-J</a> - Do not use insecure or weak cryptographic algorithms</li><li>• Derived from FindSecBugs rule <a href="#">BEAN_PROPERTY_INJECTION</a></li></ul></div> <div>Available In:</div> <div><div>sonarcloud</div><div></div><div>sonarqube</div><div></div></div>
<div>Assignment of lazy-initialized members should be the last step with double-checked locking</div> <div> Bug</div>	
<div>"String" calls should not go beyond their bounds</div> <div> Bug</div>	
<div>Raw byte values should not be used in bitwise operations in combination with shifts</div> <div> Bug</div>	

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)