

Secrets

ABAP

Apex

C

C++

CloudFormation

COBOL

C#

CSS

Flex

Go

HTML

Java

JavaScript

Kotlin

Objective C

PHP

PL/I

PL/SQL

Python

RPG

Ruby

Scala

Swift

Terraform

Text

TypeScript

T-SQL

VB.NET

VB6

XML

Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Abstract class names should comply with a naming convention

Code Smell

Strings literals should be placed on the left side when checking for equality

Code Smell

Files should contain an empty newline at the end

Code Smell

Source code should be indented consistently

Code Smell

A close curly brace should be located at the beginning of a line

Code Smell

Close curly brace and the next "else", "catch" and "finally" keywords should be on two different lines

Code Smell

Close curly brace and the next "else", "catch" and "finally" keywords should be located on the same line

Code Smell

An open curly brace should be located at the beginning of a line

Code Smell

An open curly brace should be located at the end of a line

Code Smell

Tabulation characters should not be used

Code Smell

Functions should not be defined with a variable number of arguments

Code Smell

Non-primitive fields should not be "volatile"

Analyze your code

BugMinor?multi-threading cert

Marking an array `volatile` means that the array itself will always be read fresh and never thread cached, but the items *in* the array will not be. Similarly, marking a mutable object field `volatile` means the object *reference* is `volatile` but the object itself is not, and other threads may not see updates to the object state.

This can be salvaged with arrays by using the relevant `AtomicArray` class, such as `AtomicIntegerArray`, instead. For mutable objects, the `volatile` should be removed, and some other method should be used to ensure thread-safety, such as synchronization, or `ThreadLocal` storage.

Noncompliant Code Example

```
private volatile int [] vInts; // Noncompliant
private volatile MyObj myObj; // Noncompliant
```

Compliant Solution

```
private AtomicIntegerArray vInts;
private MyObj myObj;
```

See

- [CERT, CON50-J](#) - Do not assume that declaring a reference `volatile` guarantees safe publication of the members of the referenced object





Available In:

sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-3077

1/2

<div>Local-Variable Type Inference should be used</div> <div> Code Smell</div>
<div>Migrate your tests from JUnit4 to the new JUnit5 annotations</div> <div> Code Smell</div>
<div>Track uses of disallowed classes</div> <div> Code Smell</div>
<div>Track uses of "@SuppressWarnings" annotations</div> <div> Code Smell</div>