




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154


Security Hotspot36

Code Smell389


Quick Fix42


Tags ▾


Search by name... 🔍


 Bug


"Iterator.hasNext()" should not call "Iterator.next()"





 Identical expressions should not be used on both sides of a binary operator





 Loops with at most one iteration should be refactored





 Variables should not be self-assigned





 "StringBuilder" and "StringBuffer" should not be instantiated with a character





 Methods should not be named "toString", "hashCode" or "equal"





 "Thread.run()" should not be called directly





 "equals" method overrides should accept "Object" parameters




 The Object.finalize() method should not be called




 Enabling file access for WebViews is security-sensitive





 Enabling JavaScript support for WebViews is security-sensitive


Fields in a "Serializable" class should either be transient or serializable

Analyze your code

 Code Smell

 Critical



 cwe serialization

Fields in a `Serializable` class must themselves be either `Serializable` or `transient` even if the class is never explicitly serialized or deserialized. For instance, under load, most J2EE application frameworks flush objects to disk, and an allegedly `Serializable` object with non-transient, non-serializable data members could cause program crashes, and open the door to attackers. In general a `Serializable` class is expected to fulfil its contract and not have an unexpected behaviour when an instance is serialized.

This rule raises an issue on non-`Serializable` fields, and on collection fields when they are not `private` (because they could be assigned non-`Serializable` values externally), and when they are assigned non-`Serializable` types within the class.

Noncompliant Code Example

```
public class Address {
    //...
}

public class Person implements Serializable {
    private static final long serialVersionUID = 1905122041950

    private String name;
    private Address address; // Noncompliant; Address isn't s
}
```

Compliant Solution

```
public class Address implements Serializable {
    private static final long serialVersionUID = 2405172041950
}

public class Person implements Serializable {
    private static final long serialVersionUID = 1905122041950

    private String name;
    private Address address;
}
```

Exceptions

The alternative to making all members `serializable` or `transient` is to implement special methods which take on the responsibility of properly serializing and de-serializing the object. This rule ignores classes which implement the following methods:

https://rules.sonarsource.com/java/RSPEC-1948

1/2

```
private void writeObject(java.io.ObjectOutputStream out)
    throws IOException
private void readObject(java.io.ObjectInputStream in)
    throws IOException, ClassNotFoundException;
```

See

- [MITRE, CWE-594](#) - Saving Unserializable Objects to Disk
- [Oracle Java 6, Serializable](#)
- [Oracle Java 7, Serializable](#)

Available In:

sonarlint  | sonarcloud  sonarqube 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)