




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Assertions should be complete

Code Smell

Tests should include assertions

Code Smell

Silly bit operations should not be performed

Code Smell

Child class fields should not shadow parent class fields

Code Smell

JUnit test cases should call super methods

Code Smell

TestCases should contain tests

Code Smell

Short-circuit logic should be used in boolean contexts

Code Smell

Methods and field names should not be the same or differ only by capitalization

Code Smell

Switch cases should end with an unconditional "break" statement

Code Smell

"switch" statements should not contain non-case labels

Code Smell

Future keywords should not be used as names

Code Smell

Thread suspensions should not be vulnerable to Denial of Service attacks

"wait" should not be called when multiple locks are held

Analyze your code

BugBlocker?multi-threading deadlock

When two locks are held simultaneously, a `wait` call only releases one of them. The other will be held until some other thread requests a lock on the awaited object. If no unrelated code tries to lock on that object, then all other threads will be locked out, resulting in a deadlock.

Noncompliant Code Example

```
synchronized (this.mon1) { // threadB can't enter this bloc
    synchronized (this.mon2) {
        this.mon2.wait(); // Noncompliant; threadA
    }
}
```





Available In:

sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-3046

1/2

 Vulnerability
A new session should be created during user authentication
 Vulnerability
JWT should be signed and verified with strong cipher algorithms
 Vulnerability
Cipher algorithms should be robust
 Vulnerability
Encryption algorithms should be used with secure mode and padding scheme