

Secrets

ABAP

Apex

C

C++

CloudFormation

COBOL

C#

CSS

Flex

Go

HTML

Java

JavaScript

Kotlin

Objective C

PHP

PL/I

PL/SQL

Python

RPG

Ruby

Scala

Swift

Terraform

Text

TypeScript

T-SQL

VB.NET

VB6

XML

# Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags

Search by name...

Broadcasting intents is security-sensitive

Security Hotspot

Expanding archive files without controlling resource consumption is security-sensitive

Security Hotspot

Configuring loggers is security-sensitive

Security Hotspot

Using weak hashing algorithms is security-sensitive

Security Hotspot

Using unsafe Jackson deserialization configuration is security-sensitive

Security Hotspot

Setting JavaBean properties is security-sensitive

Security Hotspot

Disabling CSRF protections is security-sensitive

Security Hotspot

Using non-standard cryptographic algorithms is security-sensitive

Security Hotspot

Using pseudorandom number generators (PRNGs) is security-sensitive

Security Hotspot

Mocking all non-private methods of a class should be avoided

Code Smell

Empty lines should not be tested with regex MULTILINE flag

Code Smell

## Server certificates should be verified during SSL/TLS connections

Analyze your code

VulnerabilityCriticalcwe privacy cert owasp ssl

Validation of X.509 certificates is essential to create secure SSL/TLS sessions not vulnerable to man-in-the-middle attacks.

The certificate chain validation includes these steps:

- The certificate is issued by its parent Certificate Authority or the root CA trusted by the system.
- Each CA is allowed to issue certificates.
- Each certificate in the chain is not expired.

This rule raises an issue when an implementation of X509TrustManager is not controlling the validity of the certificate (ie: no exception is raised). Empty implementations of the X509TrustManager interface are often created to disable certificate validation. The correct solution is to provide an appropriate trust store.

### Noncompliant Code Example

```
class TrustAllManager implements X509TrustManager {

    @Override
    public void checkClientTrusted(X509Certificate[] chain,
    }

    @Override
    public void checkServerTrusted(X509Certificate[] chain,
    LOG.log(Level.SEVERE, ERROR_MESSAGE);
    }

    @Override
    public X509Certificate[] getAcceptedIssuers() {
        return null;
    }
}
```

### See

- OWASP Top 10 2021 Category A2 - Cryptographic Failures
- OWASP Top 10 2021 Category A5 - Security Misconfiguration
- OWASP Top 10 2021 Category A7 - Identification and Authentication Failures
- OWASP Top 10 2017 Category A6 - Security Misconfiguration
- MITRE, CWE-295 - Improper Certificate Validation
- CERT, MSC61-J. - Do not use insecure or weak cryptographic algorithms




Available In:  
sonarlintsonarcloudsonarqube

https://rules.sonarsource.com/java/RSPEC-4830

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR,

1/2

SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)

<p>Methods setUp() and tearDown() should be correctly annotated starting with JUnit4</p> <p> Code Smell</p>
<p>Class members annotated with "@VisibleForTesting" should not be accessed from production code</p> <p> Code Smell</p>
<p>"String#replace" should be preferred to "String#replaceAll"</p> <p> Code Smell</p>
<p>Derived exceptions should not hide their parents' catch blocks</p>