




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags ▾

Search by name... 🔍

Assertions should not be used in production code

Bug

DateTimeFormatters should not use mismatched year and week numbers

Bug

Unicode Grapheme Clusters should be avoided inside regex character classes

Bug

Case insensitive Unicode regular expressions should enable the "UNICODE_CASE" flag

Bug

Assertions should not compare an object to itself

Bug

Regex alternatives should not be redundant

Bug

Alternatives in regular expressions should be grouped when used with anchors

Bug

AssertJ methods setting the assertion context should come before an assertion

Bug

AssertJ configuration should be applied

Bug

JUnit5 test classes and methods should not be silently ignored

Bug

"ThreadLocal" variables should be cleaned up when no longer used

Bug

Using clear-text protocols is security-sensitive

Analyze your code

Security HotspotCritical ⓘcwe owasp

Clear-text protocols such as `ftp`, `telnet` or non-secure `http` lack encryption of transported data, as well as the capability to build an authenticated connection. It means that an attacker able to sniff traffic from the network can read, modify or corrupt the transported content. These protocols are not secure as they expose applications to an extensive range of risks:

- Sensitive data exposure
- Traffic redirected to a malicious endpoint
- Malware infected software update or installer
- Execution of client side code
- Corruption of critical information

Even in the context of isolated networks like offline environments or segmented cloud environments, the insider threat exists. Thus, attacks involving communications being sniffed or tampered with can still happen.

For example, attackers could successfully compromise prior security layers by:

- Bypassing isolation mechanisms
- Compromising a component of the network
- Getting the credentials of an internal IAM account (either from a service account or an actual person)

In such cases, encrypting communications would decrease the chances of attackers to successfully leak data or steal credentials from other network components. By layering various security practices (segmentation and encryption, for example), the application will follow the *defense-in-depth* principle.

Note that using the `http` protocol is being deprecated by [major web browsers](#).

In the past, it has led to the following vulnerabilities:

- [CVE-2019-6169](#)
- [CVE-2019-12327](#)
- [CVE-2019-11065](#)

Ask Yourself Whether

- Application data needs to be protected against falsifications or leaks when transiting over the network.
- Application data transits over a network that is considered untrusted.
- Compliance rules require the service to encrypt data in transit.
- Your application renders web pages with a relaxed mixed content policy.
- OS level protections against clear-text traffic are deactivated.






There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

- Make application data transit over a secure, authenticated and encrypted protocol like TLS or SSH. Here are a few alternatives to the most common clear-text protocols:
 - Use `ssh` as an alternative to `telnet`
 - Use `sftp`, `scp` or `ftps` instead of `ftp`
 - Use `https` instead of `http`

https://rules.sonarsource.com/java/RSPEC-5332

1/3

 Bug
Strings and Boxed types should be compared using "equals()"
 Bug
InputStream.read() implementation should not return a signed byte
 Bug
"compareTo" should not be overloaded
 Bug
"iterator" should not return "this"
 Bug

- Use SMTP over SSL/TLS or SMTP with STARTTLS instead of clear-text SMTP
- Enable encryption of cloud components communications whenever it's possible.
- Configure your application to block mixed content when rendering web pages.
- If available, enforce OS level deactivation of all clear-text traffic

It is recommended to secure all transport channels (even local network) as it can take a single non secure connection to compromise an entire application or system.

Sensitive Code Example

These clients from [Apache commons net](#) libraries are based on unencrypted protocols and are not recommended:

```
TelnetClient telnet = new TelnetClient(); // Sensitive

FTPClient ftpClient = new FTPClient(); // Sensitive

SMTPClient smtpClient = new SMTPClient(); // Sensitive
```

Unencrypted HTTP connections, when using [okhttp](#) library for instance, should be avoided:

```
ConnectionSpec spec = new ConnectionSpec.Builder(ConnectionS
    .build();
```

Android WebView can be configured to allow a secure origin to load content from any other origin, even if that origin is insecure (mixed content);

```
import android.webkit.WebView

WebView webView = findViewById(R.id.webview)
webView.getSettings().setMixedContentMode(MIXED_CONTENT_ALWA
```

Compliant Solution

Use instead these clients from [Apache commons net](#) and [JSch/ssh](#) library:

```
JSch jsch = new JSch(); // Compliant

if(implicit) {
    // implicit mode is considered deprecated but offer the sa
    FTPSClient ftpsClient = new FTPSClient(true); // Compliant
}
else {
    FTPSClient ftpsClient = new FTPSClient(); // Compliant
}

if(implicit) {
    // implicit mode is considered deprecated but offer the sa
    SMTPSClient smtpsClient = new SMTPSClient(true); // Compli
}
else {
    SMTPSClient smtpsClient = new SMTPSClient(); // Compliant
    smtpsClient.connect("127.0.0.1", 25);
    if (smtpsClient.execTLS()) {
        // commands
    }
}
```

Perform HTTP encrypted connections, with [okhttp](#) library for instance:

```
ConnectionSpec spec = new ConnectionSpec.Builder(ConnectionS
    .build();
```

The most secure mode for Android WebView is MIXED_CONTENT_NEVER_ALLOW;

```
import android.webkit.WebView

WebView webView = findViewById(R.id.webview)
webView.getSettings().setMixedContentMode(MIXED_CONTENT_NEVE
```

Exceptions

No issue is reported for the following cases because they are not considered sensitive:

- Insecure protocol scheme followed by loopback addresses like 127.0.0.1 or localhost

See

- [OWASP Top 10 2021 Category A2](#) - Cryptographic Failures
- [OWASP Top 10 2017 Category A3](#) - Sensitive Data Exposure
- [Mobile AppSec Verification Standard](#) - Network Communication Requirements
- [OWASP Mobile Top 10 2016 Category M3](#) - Insecure Communication
- [MITRE, CWE-200](#) - Exposure of Sensitive Information to an Unauthorized Actor
- [MITRE, CWE-319](#) - Cleartext Transmission of Sensitive Information
- [Google, Moving towards more secure web](#)
- [Mozilla, Deprecating non secure http](#)

Available In:



© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)