

[RESTful Web Service](#)

This guide walks you through the process of creating a "hello world" [RESTful web service](#) with Spring.

What you'll do

You'll build a service that will accept HTTP GET requests at:

```
http://localhost:8080/greeting
```

and respond with a [JSON](#) representation of a greeting:

```
{"id":1,"content":"Hello, World!"}
```

You can customize the greeting with an optional `name` parameter in the query string:

```
http://localhost:8080/greeting?name=User
```

The `name` parameter value overrides the default value of "World" and is reflected in the response:

```
{"id":1,"content":"Hello, User!"}
```

What you'll need

About 15 minutes

A favorite text editor or IDE

[JDK 1.8](#) or later

[Gradle 2.3+](#) or [Maven 3.0+](#)

You can also import the code from this guide as well as view the web page directly into [Spring Tool Suite \(STS\)](#) and work your way through it from there.

How to complete this guide

Like most Spring [Getting Started guides](#), you can start from scratch and complete each step, or you can bypass basic setup steps that are already familiar to you. Either way, you end up with working code.

To **start from scratch**, move on to [Build with Gradle](#).

To **skip the basics**, do the following:

[Download](#) and unzip the source repository for this guide, or clone it using [Git](#): `git clone https://github.com/spring-guides/gs-rest-service.git`

cd into `gs-rest-service/initial`

Jump ahead to [Create a resource representation class](#).

When you're finished, you can check your results against the code in `gs-rest-service/complete`.

Gradle

First you set up a basic build script. You can use any build system you like when building apps with Spring, but the code you need to work with [Gradle](#) and [Maven](#) is included here. If you're not familiar with either, refer to [Building Java Projects with Gradle](#) or [Building Java Projects with Maven](#).

Create the directory structure

In a project directory of your choosing, create the following subdirectory structure; for example, with `mkdir -p src/main/java/hello` on *nix systems:

```
└─ src
    └─ main
        └─ java
            └─ hello
```

Create a Gradle build file

Below is the [initial Gradle build file](#).

```
build.gradle
```

```
buildscript {
    repositories {
        mavenCentral()
    }
    dependencies {
        classpath("org.springframework.boot:spring-boot-gradle-plugin:1.4.2.RELEASE")
    }
}
```

```

apply plugin: 'java'
apply plugin: 'eclipse'
apply plugin: 'idea'
apply plugin: 'org.springframework.boot'

jar {
    baseName = 'gs-rest-service'
    version = '0.1.0'
}

repositories {
    mavenCentral()
}

sourceCompatibility = 1.8
targetCompatibility = 1.8

dependencies {
    compile("org.springframework.boot:spring-boot-starter-web")
    testCompile('org.springframework.boot:spring-boot-starter-test')
}

```

The [Spring Boot gradle plugin](#) provides many convenient features:

It collects all the jars on the classpath and builds a single, runnable "über-jar", which makes it more convenient to execute and transport your service.

It searches for the `public static void main()` method to flag as a runnable class.

It provides a built-in dependency resolver that sets the version number to match [Spring Boot dependencies](#). You can override any version you wish, but it will default to Boot's chosen set of versions.

Maven

First you set up a basic build script. You can use any build system you like when building apps with Spring, but the code you need to work with [Maven](#) is included here. If you're not familiar with Maven, refer to [Building Java Projects with Maven](#).

Create the directory structure

In a project directory of your choosing, create the following subdirectory structure; for example, with `mkdir -p src/main/java/hello` on *nix systems:

```
└─ src
```

```
└─ main
    └─ java
        └─ hello
```

pom.xml

```
<?xml version="1.0" encoding="UTF-8"?>
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0 http://maven.apache.org/xsd/maven-
4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <groupId>org.springframework</groupId>
  <artifactId>gs-rest-service</artifactId>
  <version>0.1.0</version>

  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
    <version>1.4.2.RELEASE</version>
  </parent>

  <dependencies>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-web</artifactId>
    </dependency>
    <dependency>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-starter-test</artifactId>
      <scope>test</scope>
    </dependency>
    <dependency>
      <groupId>com.jayway.jsonpath</groupId>
      <artifactId>json-path</artifactId>
      <scope>test</scope>
    </dependency>
  </dependencies>

  <properties>
    <java.version>1.8</java.version>
  </properties>
```

```

<build>
  <plugins>
    <plugin>
      <groupId>org.springframework.boot</groupId>
      <artifactId>spring-boot-maven-plugin</artifactId>
    </plugin>
  </plugins>
</build>

<repositories>
  <repository>
    <id>spring-releases</id>
    <url>https://repo.spring.io/libs-release</url>
  </repository>
</repositories>
<pluginRepositories>
  <pluginRepository>
    <id>spring-releases</id>
    <url>https://repo.spring.io/libs-release</url>
  </pluginRepository>
</pluginRepositories>
</project>

```

The [Spring Boot Maven plugin](#) provides many convenient features:

It collects all the jars on the classpath and builds a single, runnable "über-jar", which makes it more convenient to execute and transport your service.

It searches for the `public static void main()` method to flag as a runnable class.

It provides a built-in dependency resolver that sets the version number to match [Spring Boot dependencies](#). You can override any version you wish, but it will default to Boot's chosen set of versions.

IDE

- Read how to import this guide straight into [Spring Tool Suite](#).
- Read how to work with this guide in [IntelliJ IDEA](#).

Create a resource representation class

Now that you've set up the project and build system, you can create your web service.

Begin the process by thinking about service interactions.

The service will handle `GET` requests for `/greeting`, optionally with a `name` parameter in the query string. The `GET` request should return a `200 OK` response with JSON in the body that represents a greeting. It should look something like this:

```
{
  "id": 1,
  "content": "Hello, World!"
}
```

The `id` field is a unique identifier for the greeting, and `content` is the textual representation of the greeting.

To model the greeting representation, you create a resource representation class. Provide a plain old java object with fields, constructors, and accessors for the `id` and `content` data:

```
src/main/java/hello/Greeting.java
```

```
package hello;

public class Greeting {

    private final long id;
    private final String content;

    public Greeting(long id, String content) {
        this.id = id;
        this.content = content;
    }

    public long getId() {
        return id;
    }

    public String getContent() {
        return content;
    }
}
```

As you see in steps below, Spring uses the [Jackson JSON](#) library to automatically marshal instances of type `Greeting` into JSON.

Next you create the resource controller that will serve these greetings.

Create a resource controller

In Spring's approach to building RESTful web services, HTTP requests are handled by a controller. These components are easily identified by the `@RestController` annotation, and the `GreetingController` below handles `GET` requests for `/greeting` by returning a new instance of the `Greeting` class:

```
src/main/java/hello/GreetingController.java
```

```
package hello;
```

```
import java.util.concurrent.atomic.AtomicLong;
import org.springframework.web.bind.annotation.RequestMapping;
import org.springframework.web.bind.annotation.RequestParam;
import org.springframework.web.bind.annotation.RestController;
```

```
@RestController
```

```
public class GreetingController {
```

```
    private static final String template = "Hello, %s!";
    private final AtomicLong counter = new AtomicLong();
```

```
    @RequestMapping("/greeting")
```

```
    public Greeting greeting(@RequestParam(value="name", defaultValue="World") String name) {
        return new Greeting(counter.incrementAndGet(),
            String.format(template, name));
    }
}
```

This controller is concise and simple, but there's plenty going on under the hood. Let's break it down step by step.

The `@RequestMapping` annotation ensures that HTTP requests to `/greeting` are mapped to the `greeting()` method.

The above example does not specify `GET` vs. `PUT`, `POST`, and so forth, because `@RequestMapping` maps all HTTP operations by default.

Use `@RequestMapping(method=GET)` to narrow this mapping.

`@RequestParam` binds the value of the query string parameter `name` into the `name` parameter of the `greeting()` method. This query string parameter is explicitly marked as optional (`required=true` by default): if it is absent in the request, the `defaultValue` of "World" is used.

The implementation of the method body creates and returns a new `Greeting` object with `id` and `content` attributes based on the next value from the `counter`, and formats the given `name` by using the greeting `template`.

A key difference between a traditional MVC controller and the RESTful web service controller above is the way that the HTTP response body is created. Rather than relying on a [view technology](#) to perform server-side rendering of the greeting data to HTML, this RESTful web service controller simply populates and returns a `Greeting` object. The object data will be written directly to the HTTP response as JSON.

This code uses Spring 4's new `@RestController` annotation, which marks the class as a controller where every method returns a domain object instead of a view. It's shorthand for `@Controller` and `@ResponseBody` rolled together.

The `Greeting` object must be converted to JSON. Thanks to Spring's HTTP message converter support, you don't need to do this conversion manually. Because [Jackson 2](#) is on the classpath, Spring's `MappingJackson2HttpMessageConverter` is automatically chosen to convert the `Greeting` instance to JSON.

Make the application executable

Although it is possible to package this service as a traditional [WAR](#) file for deployment to an external application server, the simpler approach demonstrated below creates a standalone application. You package everything in a single, executable JAR file, driven by a good old Java `main()` method. Along the way, you use Spring's support for embedding the [Tomcat](#) servlet container as the HTTP runtime, instead of deploying to an external instance.

```
src/main/java/hello/Application.java
```

```
package hello;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class Application {

    public static void main(String[] args) {
        SpringApplication.run(Application.class, args);
    }
}
```



```
}
```

`@SpringBootApplication` is a convenience annotation that adds all of the following:

`@Configuration` tags the class as a source of bean definitions for the application context.

`@EnableAutoConfiguration` tells Spring Boot to start adding beans based on classpath settings, other beans, and various property settings.

Normally you would add `@EnableWebMvc` for a Spring MVC app, but Spring Boot adds it automatically when it sees **spring-webmvc** on the classpath. This flags the application as a web application and activates key behaviors such as setting up a `DispatcherServlet`.

`@ComponentScan` tells Spring to look for other components, configurations, and services in the `hello` package, allowing it to find the controllers.

The `main()` method uses Spring Boot's `SpringApplication.run()` method to launch an application. Did you notice that there wasn't a single line of XML? No **web.xml** file either. This web application is 100% pure Java and you didn't have to deal with configuring any plumbing or infrastructure.

Build an executable JAR

You can run the application from the command line with Gradle or Maven. Or you can build a single executable JAR file that contains all the necessary dependencies, classes, and resources, and run that. This makes it easy to ship, version, and deploy the service as an application throughout the development lifecycle, across different environments, and so forth.

If you are using Gradle, you can run the application using `./gradlew bootRun`. Or you can build the JAR file using `./gradlew build`. Then you can run the JAR file:

```
java -jar build/libs/gs-rest-service-0.1.0.jar
```

If you are using Maven, you can run the application using `./mvnw spring-boot:run`. Or you can build the JAR file with `./mvnw clean package`. Then you can run the JAR file:

```
java -jar target/gs-rest-service-0.1.0.jar
```

The procedure above will create a runnable JAR. You can also opt to [build a classic WAR file](#) instead.

Logging output is displayed. The service should be up and running within a few seconds.

Test the service

Now that the service is up, visit <http://localhost:8080/greeting>, where you see:

```
{"id":1,"content":"Hello, World!"}
```

Provide a `name` query string parameter with <http://localhost:8080/greeting?name=User>. Notice how the value of the `content` attribute changes from "Hello, World!" to "Hello User!":

```
{"id":2,"content":"Hello, User!"}
```

This change demonstrates that the `@RequestParam` arrangement in `GreetingController` is working as expected. The `name` parameter has been given a default value of "World", but can always be explicitly overridden through the query string.

Notice also how the `id` attribute has changed from `1` to `2`. This proves that you are working against the same `GreetingController` instance across multiple requests, and that its `counter` field is being incremented on each call as expected.

Summary

Congratulations! You've just developed a RESTful web service with Spring.

Want to write a new guide or contribute to an existing one? Check out our [contribution guidelines](#).

All guides are released with an ASLv2 license for the code, and an [Attribution, NoDerivatives creative commons license](#) for the writing.