

Secrets

ABAP

Apex

C

C++

CloudFormation

COBOL

C#

CSS

Flex

Go

HTML

Java

JavaScript

Kotlin

Objective C

PHP

PL/I

PL/SQL

Python

RPG

Ruby

Scala

Swift

Terraform

Text

TypeScript

T-SQL

VB.NET

VB6

XML

Java

Java

Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36

Code Smell389

Quick Fix42

Tags

Search by name...

Security Hotspot

Allowing deserialization of LDAP objects is security-sensitive

Setting loose POSIX file permissions is security-sensitive

Formatting SQL queries is security-sensitive

Deprecated annotations should include explanations

Restricted Identifiers should not be used as Identifiers

Redundant constructors/methods should be avoided in records

Records should be used instead of ordinary classes when representing immutable data structure

"Stream.toList()" method should be used instead of "collectors" when unmodifiable list needed

Operator "instanceof" should be used instead of "A.class.isInstance()"

String multiline concatenation should be replaced with Text Blocks

Single-character alternations in regular expressions should be

XML operations should not be vulnerable to injection attacks

Analyze your code

Vulnerability

Major

injection cwe owasp

User-provided data, such as URL parameters, POST data payloads, or cookies, are tainted with user-controlled inputs. Therefore, they should always be considered untrusted.

XML injection occurs when user-controlled input is embedded into XML syntax. In such a scenario, an attacker can abuse the XML syntax and inject arbitrary XML elements. This can lead to cross-site scripting issues or denial-of-service attacks.

In addition, the application may parse the XML document with a weakly configured XML parser (namely, a parser with external entity support enabled). In this case, an XML External Entity (XXE) injection would expose the application to sensitive file disclosure or server-side request forgeries (SSRF).

An attacker can also elevate privileges if the XML data is used for authentication.

Noncompliant Code Example

```
protected void doGet(HttpServletRequest req, HttpServletResponse res) {
    String id = req.getParameter("id");
    String xml = "<node id=\"" + id + "\"></node>";
    FileOutputStream fos = new FileOutputStream("output.xml");
    fos.write(xml.getBytes(Charset.forName("UTF-8")));
}
```

javax.xml.parsers.DocumentBuilder

```
protected void doGet(HttpServletRequest req, HttpServletResponse res) {
    String id = req.getParameter("id");
    String xml = "<node id=\"" + id + "\"></node>";
    DocumentBuilderFactory factory = DocumentBuilderFactory.newInstance();
    DocumentBuilder builder = factory.newDocumentBuilder();
    Document doc = builder.parse(new InputSource(new StringReader(xml)));
}
```

Compliant Solution





```
protected void doGet(HttpServletRequest req, HttpServletResponse res) {
    String id = req.getParameter("id");
    if(id.matches("[A-Za-z0-9_]+$")) {
        String xml = "<node id=\"" + id + "\"></node>";
        FileOutputStream fos = new FileOutputStream("output.xml");
        fos.write(xml.getBytes(Charset.forName("UTF-8")));
    }
}
```

javax.xml.parsers.DocumentBuilder

```
protected void doGet(HttpServletRequest req, HttpServletResponse res) {
    String id = req.getParameter("id");
    String xml = "<node></node>";
}
```

https://rules.sonarsource.com/java/RSPEC-6399

1/2

replaced with character classes
 Code Smell
Reluctant quantifiers in regular expressions should be followed by an expression that can't match the empty string
 Code Smell
Constructors of an "abstract" class should not be declared "public"
 Code Smell
Similar tests should be grouped in a single Parameterized test
 Code Smell

```
DocumentBuilderFactory factory = DocumentBuilderFactory.  
DocumentBuilder builder = factory.newDocumentBuilder();  
Document doc = builder.parse(new InputSource(new StringReader("  
Element element = (Element) doc.getElementsByTagName("so  
element.setAttribute("id", req.getParameter("id"));  
}
```

See

- [OWASP Top 10 2021 Category A3](#) - Injection
- [OWASP Top 10 2017 Category A1](#) - Injection
- [MITRE, CWE-20](#) - Improper Input Validation
- [MITRE, CWE-76](#) - Improper Neutralization of Equivalent Special Elements

Available In:
 |  Developer Edition