




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 **Java**


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



## Java static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVA code

All rules632

Vulnerability53

Bug154

Security Hotspot36


Code Smell389

Quick Fix42


Tags ▾

Search by name... 🔍


not be left unused

 Bug


All branches in a conditional structure should not have exactly the same implementation

 Bug


Optional value should only be accessed after calling isPresent()

 Bug


Overrides should match their parent class methods in synchronization

 Bug


Value-based classes should not be used for locking

 Bug


Expressions used in "assert" should not produce side effects

 Bug


"volatile" variables should not be used with compound operators

 Bug


"getClass" should not be used for synchronization

 Bug


Min and max used in combination should not always return the same value

 Bug


Assignment of lazy-initialized members should be the last step with double-checked locking

 Bug

"String" calls should not go beyond their bounds

 Bug

Boolean values should not be used in

 Bug

### Using non-standard cryptographic algorithms is security-sensitive

Analyze your code

Security Hotspot

Critical

cwe sans-top25 owasp

The use of a non-standard algorithm is dangerous because a determined attacker may be able to break the algorithm and compromise whatever data has been protected. Standard algorithms like SHA-256, SHA-384, SHA-512, ... should be used instead.

This rule tracks creation of `java.security.MessageDigest` subclasses.

#### Recommended Secure Coding Practices

- Use a standard algorithm instead of creating a custom one.

#### Sensitive Code Example

```
public class MyCryptographicAlgorithm extends MessageDigest
{
    ...
}
```

#### Compliant Solution

```
MessageDigest digest = MessageDigest.getInstance("SHA-256");
```

#### See

- OWASP Top 10 2021 Category A2 - Cryptographic Failures
- OWASP Top 10 2017 Category A3 - Sensitive Data Exposure
- MITRE, CWE-327 - Use of a Broken or Risky Cryptographic Algorithm
- SANS Top 25 - Porous Defenses
- Derived from FindSecBugs rule [MessageDigest is Custom](#)

Available In:





sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/java/RSPEC-2257

1/2

<div>raw byte values should not be used in bitwise operations in combination with shifts</div> <div> Bug</div>
<div>Getters and setters should be synchronized in pairs</div> <div> Bug</div>
<div>Non-thread-safe fields should not be static</div> <div> Bug</div>
<div>"null" should not be used with "Optional"</div> <div> Bug</div>