




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



## TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51

Security Hotspot 43

Code Smell 158

Quick Fix 50

Tags ▾

Search by name... 🔍

Files should not have too many lines of code

Code Smell

Lines should not be too long

Code Smell

Debugger statements should not be used

Vulnerability

Regular expressions using Unicode character classes or property escapes should enable the unicode flag

Bug

The base should be provided to "parseInt"

Bug

Function declarations should not be made within blocks

Bug

Writing cookies is security-sensitive

Security Hotspot

"continue" should not be used

Code Smell

Primitive return types should be used

Code Smell

Default type parameters should be omitted

Code Smell

Type assertions should use "as"

Code Smell

Method overloads should be grouped together

Code Smell

Interfaces should not be empty

Unused assignments should be removed

Analyze your code

Code Smell

Major ?

cwe unused

A dead store happens when a local variable is assigned a value that is not read by any subsequent instruction. Calculating or retrieving a value only to then overwrite it or throw it away, could indicate a serious error in the code. Even if it's not an error, it is at best a waste of resources. Therefore all calculated values should be used.

**Noncompliant Code Example**

```
i = a + b; // Noncompliant; calculation result not used before
i = compute();
```

**Compliant Solution**

```
i = a + b;
i += compute();
```

**Exceptions**

This rule ignores initializations to -1, 0, 1, null, undefined, [], {}, true, false and "". Variables that start with an underscore (e.g. '\_unused') are ignored.

This rule also ignores variables declared with object destructuring using rest syntax (used to exclude some properties from object):

```
let {a, b, ...rest} = obj; // 'a' and 'b' are ok
doSomething(rest);

let [x1, x2, x3] = arr;    // but 'x1' is noncompliant, as o
doSomething(x2, x3);
```

**See**

- [MITRE, CWE-563](#) - Assignment to Variable without Use ("Unused Variable")

Available In:

sonarlint

sonarcloud





sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-1854

1/2

 Code Smell
Trailing commas should be used
 Code Smell
"import" should be used to include external code
 Code Smell
Braces and parentheses should be used consistently with arrow functions
 Code Smell
Destructuring syntax should be used for assignments