



# jQuery Plugins

# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

Not Interested

European Getaway

SHOW PRICE

Visit Japan

SHOW PRICE

# Setting up a Plugin - HTML

index.html

```
<li class='vacation' data-price='399'>  
  <h3>Hawaiian Vacation</h3>  
  <button>Show Price</button>  
  <a href='#' class='not-interested'>Not Interested</a>  
</li>
```

*When clicked, we'll add a <p> with the price*

*Clicking "Not Interested" will hide the vacation*

# Setting up a Plugin

application.js


*Makes the priceify method available*

```
$.fn.priceify = function() {  
  console.log('Pricify Called');  
  console.log(this);  
};
```

*Within the plugin, 'this' will be the jQuery object the plugin was called on*


```
$('.vacation').priceify();
```

*We can 'priceify' all vacations at once*



# Adding a click handler to append price details

application.js

```
$.fn.priceify = function() {  
    var vacation = this;  'this' will be $$('.vacation')  
    vacation.on('click.priceify', 'button', function() {  
        var price = vacation.data('price');  
        var details = $('<p>Book 3 days for $'+(3 * price)+'</p>');  
        $(this).hide();  
        vacation.append(details);  
    });  
};  
  
$(document).ready(function() {  
    $('<div>vacation</div>').priceify();  
});
```



# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

Not Interested

European Getaway

SHOW PRICE


Visit Japan

SHOW PRICE

# Fixing the vacation plugin

application.js

*'this' will point to all .vacation elements*



```
$.fn.priceify = function() {  
  var vacation = this;  
  vacation.on('click.priceify', 'button', function() {  
    var price = vacation.data('price');  
    var details = $('<p>Book 3 days for $'+(3 * price)+'</p>');  
    $(this).hide();  
    vacation.append(details);  
  });  
};  
  
$(document).ready(function() {  
  $('<div>.vacation</div>').priceify();  
});
```

*When we call append, it'll append it in multiple places!*

# Adding Iteration

*Loop over each .vacation element  
setting each one to 'this'*

application.js

```
$.fn.priceify = function() {  
  this.each(function() {  
    var vacation = this;  
    vacation.on('click.priceify', 'button', function() {  
      var price = vacation.data('price');  
      var details = $('<p>Book 3 days for $'+(3 * price)+'</p>');  
      $(this).hide();  
      vacation.append(details);  
    });  
  });  
};
```

*jQuery Object Method*

each(<function>)

*Each vacation has its own click handler  
and local variable scope*



# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

Not Interested

European Getaway

SHOW PRICE

Visit Japan

SHOW PRICE

# Plugins with Parameters

## Plugin Use With Options

```
$('.vacation').priceify({ days: 5 });
```



*Let's make our plugin accept an argument*

```
$.fn.priceify = function(options) {  
    ...  
    var price = vacation.data('price');  
    var details = $('<p>Book ' + options.days + ' days for $' +  
        (options.days * price) + '</p>');
```

But what if we wanted to make it an optional parameter?

*Default it to 3 days if not passed in*

# Plugins with Options

## Plugin Use With Options

```
$( '.vacation' ).priceify({ days: 5 });
```

## Plugin Use Without Options

```
$( '.vacation' ).priceify();
```

*Let's make our plugin accept an optional argument*

```
$.fn.priceify = function(options) { ... };
```

# Using \$.extend

*Utility Method*

```
$.extend(target[, object1][, objectn])
```

*Will combine all objects*

```
$.extend({ days: 3 }, { price: 5 });
```



```
{ days: 3, price: 5 }
```

```
$.extend({ days: 3 }, {});
```



```
{ days: 3 }
```

```
$.extend({ days: 3 }, { days: 5 });
```



```
{ days: 5 }
```



*That's how we can set a default value*

# Using \$.extend in our plugin

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend({ days: 3 }, options);  
  
    ...  
    var vacation = this;  
    var price = vacation.data('price');
```

*Sets the default days to 3*

*Why not include the rest of these setting variables inside the settings object?*



# \$.extend

application.js

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend({  
      days: 3,  
      vacation: this,  
      price: $(this).data('price')  
    }, options);  
    vacation.on('click.priceify', 'button', function() { ... });  
  });  
};
```



*Our event handler will need to be updated too*

settings.vacation


settings.days

settings.price

# \$.extend

application.js

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend({  
      days: 3,  
      vacation: this,  
      price: $(this).data('price')  
    }, options);  
  
    settings.vacation.on('click.priceify', 'button', function() {  
      var details = $('<p>Book ' + settings.days + ' days for $' + (settings.days *  
settings.price + '</p>');  
      $(this).hide();  
      settings.vacation.append(details);  
    });  
  });  
};
```



# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

Not Interested

European Getaway

SHOW PRICE

Visit Japan

SHOW PRICE

# Calling a Plugin from Outside

index.html


*We could trigger('click.priceify') on all buttons*

```
<a href='#' class='show-prices'>Show All Prices</a>
```



application.js

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend(...);  
    settings.vacation.on('click.priceify', 'button', function() {  
      var details = $('<p>Book ' + settings.days + ' days for $' +  
        (settings.days * settings.price) + '</p>');  
      $(this).hide();  
      settings.vacation.append(details);  
    });  
  });  
};
```



*... but we should create a new event  
and call this same function*

# Splitting out the show function

index.html

```
<a href='#' class='show-prices'>Show All Prices</a>
```

application.js

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend(...);  
    var show = function() {  
      var details = $('<p>Book ' + settings.days + ' days for $' +  
        (settings.days * settings.price) + '</p>');  
      $(this).hide();  
      settings.vacation.append(details);  
    };  
    settings.vacation.on('click.priceify', 'button', show);  
  });  
};
```

*Split out the show function*





# Calling a Plugin from Outside

index.html

```
<a href='#' class='show-prices'>Show All Prices</a>
```

application.js

```
$.fn.priceify = function(options) {  
  this.each(function() {  
    var settings = $.extend(...);  
    var show = function() { ... };  
    settings.vacation.on('click.priceify', 'button', show);  
    settings.vacation.on('show.priceify', show);  
  });  
};
```

*We can use the same show method*

*Custom Event*

```
$('.show-prices').on('click', function(event) {  
  event.preventDefault();  
  $('.vacation').trigger('show.priceify');  
});
```

*Trigger an event on the vacation  
that the plugin watches for*

# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

European Getaway

SHOW PRICE

Visit Japan

SHOW PRICE

# Removing behavior of a plugin

index.html

```
<li class="vacation" data-price='399'>
  ...
  <a href='#' class='remove-vacation'>Not Interested</a>
</li>
```

application.js

```
$.fn.priceify = function(options) {
  ...
  var remove = function() {
    settings.vacation.hide().off('.priceify');
  };
  settings.vacation.on('click.priceify', '.remove-vacation', remove);
};
```

*Removes all \*.priceify event handlers*



# jQuery Travels - Vacation Packages

## Packages

Show All Prices

Hawaiian Vacation

SHOW PRICE

European Getaway

SHOW PRICE

Visit Japan

SHOW PRICE

Not Interested