




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 **JavaScript**


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

All rules 285

Vulnerability 29

Bug 62

Security Hotspot 43

Code Smell 151

Quick Fix 41

Tags ▾

Search by name... 🔍

Code Smell

Extra semicolons should be removed

Code Smell

Class names should comply with a naming convention

Code Smell

Track uses of "TODO" tags

Code Smell

Web SQL databases should not be used

Vulnerability

Variables should be defined before being used

Bug

Variables declared with "var" should be declared before they are used

Code Smell

Track lack of copyright and license headers

Code Smell

Reading the Standard Input is security-sensitive

Security Hotspot

Using command line arguments is security-sensitive

Security Hotspot

Using Sockets is security-sensitive

Security Hotspot

Executing XPath expressions is security-sensitive

Security Hotspot

Encrypting data is security-sensitive

Security Hotspot

Regular expressions should not contain empty groups

Analyze your code

Code Smell

Major

regex

There are several reasons to use a group in a regular expression:

- to change the precedence (e.g. `do(g|or)` will match 'dog' and 'door')
- to remember parenthesised part of the match in the case of capturing group
- to improve readability

In any case, having an empty group is most probably a mistake. Either it is a leftover after refactoring and should be removed, or the actual parentheses were intended and were not escaped.

Noncompliant Code Example

```
const dateRegex = /^(?0[1-9]|[12][0-9]|3[01])[ - .](?0[1-9]
const methodCallRegex = /foo()/; // Noncompliant, will match
```

Compliant Solution

```
const dateRegex = /^(?0[1-9]|[12][0-9]|3[01])[ - .](?0[1-9]
const methodCallRegex = /foo\(\)/; // OK, matches 'foo()'
```

Available In:

sonarlint





sonarcloud

sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/javascript/RSPEC-6331

1/2

<div>Using regular expressions is security-sensitive</div> <div> Security Hotspot</div>
<div>Class methods should be used instead of "prototype" assignments</div> <div> Code Smell</div>
<div>Function constructors should not be used</div> <div> Code Smell</div>
<div>Variables should be declared with "let" or "const"</div> <div> Code Smell</div>