

# Acting on Interaction

## Passing in a function

```
$(document).ready(<event handler function>);
```

The ready method takes an event handler function as argument

```
function() {
   // executing the function runs the code
   // between the braces
}
```

We create a function with the function keyword

```
$(document).ready(function() {
   // this function runs when the DOM is ready
});
```

And we pass this function as an argument to the ready method.

3.2 Acting on Interaction





### Vacation Packages

¡Query Air Atlantic

#### Hawaiian Vacation

Comments on this deal:

"Amazing Deal!"

"Can't wait to take this trip!"

**GET PRICE** 

b

Call us at 1-555-jquery-air to make a reservation today!

## Watching for Click

```
application.js
$(document).ready(function() {
  // runs when the DOM is ready
});
          Target all buttons
                             Watch for any clicks
$('button').on('click', function() {
  // runs when any button is clicked
});
                   Run the code inside of this function
```



jQuery Object Methods

.on(<event>, <event handler>)

## Removing from the DOM

```
$ runs when the DOM is ready
$ (document).ready(function() {
    $('button').on('click', function() {
        // run this function on click
    });
});

runs when a button is clicked
```

```
DOCUMENT

li class="vacation"

h2


Hawaiian Vacation


button

Get Price
```

## Removing from the DOM

```
$ (document).ready(function() {
    $('button').on('click', function() {
       var price = $('From $399.99');
       $('.vacation').append(price);
       $('button').remove();
    });
});
```





Now the price will be shown when we click the button

