




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51


Security Hotspot 43

Code Smell 158


Quick Fix 50


Tags ▾


Search by name... 🔍


 Security Hotspot


Disabling auto-escaping in template engines is security-sensitive


 Security Hotspot


 Using shell interpreter when executing OS commands is security-sensitive


 Setting loose POSIX file permissions is security-sensitive


 Formatting SQL queries is security-sensitive


 Comma operator should not be used


 Regular expressions should not contain empty groups

 Regular expressions should not contain multiple spaces

 Chai assertions should have only one reason to succeed


 Single-character alternations in regular expressions should be replaced with character classes


 Reluctant quantifiers in regular expressions should be followed by an expression that can't match the empty string


 Tests should check which exception is thrown


Conditionals should start on new lines

Analyze your code

 Code Smell

 Critical

 Quick Fix

 suspicious

Code is clearest when each statement has its own line. Nonetheless, it is a common pattern to combine on the same line an *if* and its resulting *then* statement. However, when an *if* is placed on the same line as the closing *}* from a preceding *then*, *else* or *else if* part, it is either an error - *else* is missing - or the invitation to a future error as maintainers fail to understand that the two statements are unconnected.

Noncompliant Code Example

```
if (condition1) {
  // ...
} if (condition2) { // Noncompliant
  //...
}
```




Compliant Solution

```
if (condition1) {
  // ...
} else if (condition2) {
  //...
}
```

Or

```
if (condition1) {
  // ...
}





if (condition2) {
  //...
}
```

Available In:
 |  | 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-3972

1/2

<div> Code Smell</div>
<div><div>Character classes in regular expressions should not contain the same character twice</div><div> Code Smell</div></div>
<div><div>Names of regular expressions named groups should be used</div><div> Code Smell</div></div>
<div><div>Regular expressions should not be too complicated</div><div> Code Smell</div></div>
<div><div>Optional property declarations should not use both '?' and 'undefined' syntax</div></div>