




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



## TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51

Security Hotspot 43

Code Smell 158

Quick Fix 50

Tags ▾

Search by name... 🔍

Allowing browsers to sniff MIME types is security-sensitive

Security Hotspot

Disabling content security policy frame-ancestors directive is security-sensitive

Security Hotspot

Allowing mixed-content is security-sensitive

Security Hotspot

Disabling content security policy fetch directives is security-sensitive

Security Hotspot

Disabling resource integrity features is security-sensitive

Security Hotspot

Disclosing fingerprints from web application technologies is security-sensitive

Security Hotspot

Having a permissive Cross-Origin Resource Sharing policy is security-sensitive

Security Hotspot

Delivering code in production with debug features activated is security-sensitive

Security Hotspot

Creating cookies without the "HttpOnly" flag is security-sensitive

Security Hotspot

Creating cookies without the "secure" flag is security-sensitive

Security Hotspot

Using hardcoded IP addresses is security-sensitive

Security Hotspot

### Objects should not be created to be dropped immediately without being used

Analyze your code

Bug Major ?

There is no good reason to create a new object to not do anything with it. Most of the time, this is due to a missing piece of code and so could lead to an unexpected behavior in production.

If it was done on purpose because the constructor has side-effects, then that side-effect code should be moved into a separate method and called directly.

#### Noncompliant Code Example

```
new MyConstructor(); // Non-Compliant
```

#### Compliant Solution

```
var something = new MyConstructor(); // Compliant
```

#### Exceptions

Immediately dropped new objects inside try-statements are ignored.

```
try {
  new MyConstructor();
} catch (e) {
  /* ... */
}
```

Available In:





sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-1848

1/2

<div><div>Regular expression quantifiers and character classes should be used concisely</div><div> Code Smell</div></div>
<div><div>Regular expression literals should be used when possible</div><div> Code Smell</div></div>
<div><div>"await" should not be used redundantly</div><div> Code Smell</div></div>
<div><div>Redundant casts and non-null assertions should be avoided</div><div> Code Smell</div></div>