

Sed sed orci. Nulla
Donec a turpis in

Collections

- LEVEL 5 -



Donec a
sed sed orci.
ipis in erat
ma. tur



Sed sed orci. Nullam a lac
Donec a turpis in erat cur
fringit. Sed sed orci. Nullam

Set of Models

```
var todoItem1 = new TodoItem();  
var todoItem2 = new TodoItem();  
var todoList = [todoItem1, todoItem2];
```



```
var TodoList = Backbone.Collection.extend({  
  model: TodoItem  
});  
var todoList = new TodoList();
```



TodoList manages a set of
TodoItem model instances

Add/Remove/Get

get number of models

```
todoList.length;
```

--> 2

add a model instance

```
todoList.add(todoItem1);
```

get model instance at index 0

```
todoList.at(0);
```

-->

```
todoItem1
```

get by id 1

```
todoList.get(1);
```

-->

```
todoItem1
```

removing a model instance

```
todoList.remove(todoItem1);
```


Bulk Population

reset

```
var todos = [  
  {description: 'Pick up milk.', status: 'incomplete'},  
  {description: 'Get a car wash', status: 'incomplete'},  
  {description: 'Learn Backbone', status: 'incomplete'}  
];  
  
todoList.reset(todos);
```

todoList

TodoItem

TodoItem

TodoItem

Each object in Array becomes a TodoItem

Collections

Backbone.js

fetching Data from the Server

URL to get JSON data from

```
var TodoList = Backbone.Collection.extend({  
  url: '/todos'  
});
```

populate collection from server

```
todoList.fetch();
```

GET /todos

```
[  
  {description: 'Pick up milk.', status: 'incomplete', id: 1},  
  {description: 'Get a car wash', status: 'incomplete', id: 2}  
]
```

```
todoList.length; ---> 2
```

Collections



Collections Can Have Events

To listen for an event on a collection

```
todoList.on('event-name', function(){  
  alert('event-name happened!');  
});
```

Run the event

```
todoList.trigger('event-name');
```




Works just like models!

Special Events

listen for reset

```
todoList.on('reset', doThing);
```

```
var doThing = function() {  
  ...  
}
```



Event triggered on reset & fetch

```
todoList.fetch();  
todoList.reset();
```

without notification

```
todoList.fetch({silent: true});  
todoList.reset({silent: true});
```

Remove event listener

```
todoList.off('reset', doThing);
```



Special Events on Collection

```
todoList.on(<event>, <function>);
```

Built-in Events

add	<i>When a model is added</i>
remove	<i>When a model is removed</i>
reset	<i>When reset or fetched</i>

```
todoList.on('add', function(todoItem){  
  ...  
});
```



todoItem is the model being added

Model Events

Models in collection

change	<i>When an attribute is modified</i>
change:<attr>	<i>When <attr> is modified</i>
destroy	<i>When a model is destroyed</i>
sync	<i>Whenever successfully synced</i>
error	<i>When an attribute is modified</i>
all	<i>When an attribute is modified</i>

Events triggered on a model in a collection will also be triggered on the collection


Iteration

Setup our collection

```
todoList.reset([  
  {description: 'Pick up milk.', status: 'incomplete', id: 1},  
  {description: 'Get a car wash.', status: 'complete', id: 2}  
]);
```

Alert each model's description

```
todoList.forEach(function(todoItem){  
  alert(todoItem.get('description'));  
});
```



Iteration continued

Build an array of descriptions

```
todoList.map(function(todoItem){  
  return todoItem.get('description');  
});
```

--> ['Pick up milk.', 'Get a car wash']

Filter models by some criteria

```
todoList.filter(function(todoItem){  
  return todoItem.get('status') === "incomplete";  
});
```

Returns array of items
that are incomplete

Other Iteration functions

forEach	reduce	reduceRight
find	filter	reject
every	all	some
include	invoke	max
min	sortBy	groupBy
sortedIndex	shuffle	toArray
size	first	initial
rest	last	without
indexOf	lastIndexOf	isEmpty
chain		

<http://documentcloud.github.com/backbone/#Collection-Underscore-Methods>