




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

- All rules 279
- Vulnerability 27
- Bug 51
- Security Hotspot 43
- Code Smell 158
- Quick Fix 50

Code Smell
Nested blocks of code should not be left empty
Code Smell
Functions should not have too many parameters
Code Smell
OS commands should not be vulnerable to argument injection attacks
Vulnerability
Repeated patterns in regular expressions should not match the empty string
Bug
Empty collections should not be accessed or iterated
Bug
"delete" should be used only with object properties
Bug
Function parameters, caught exceptions and foreach variables' initial values should not be ignored
Bug
Forwarding client IP address is security-sensitive
Security Hotspot
Allowing confidential information to be logged is security-sensitive
Security Hotspot
Allowing browsers to perform DNS prefetching is security-sensitive
Security Hotspot
Disabling Certificate Transparency monitoring is security-sensitive

"new" operators should be used with functions

Analyze your code

Bug Major

The new keyword should only be used with objects that define a constructor function. Use it with anything else, and you'll get a `TypeError` because there won't be a constructor function for the new keyword to invoke.

Noncompliant Code Example

```
function MyClass() {
  this.foo = 'bar';
}

var someClass = 1;

var obj1 = new someClass; // Noncompliant;
var obj2 = new MyClass(); // Noncompliant if considerJSDo
```

Compliant Solution

```
/**
 * @constructor
 */
function MyClass() {
  this.foo = 'bar';
}





var someClass = function(){
  this.prop = 1;
}

var obj1 = new someClass; // Compliant
var obj2 = new MyClass(); // Compliant regardless of consid
```

Available In:

sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.  
[Privacy Policy](#)

<div>monitoring is security-sensitive</div> <div> Security Hotspot</div>
<div>Disabling Strict-Transport-Security policy is security-sensitive</div> <div> Security Hotspot</div>
<div>Disabling strict HTTP no-referrer policy is security-sensitive</div> <div> Security Hotspot</div>
<div>Allowing browsers to sniff MIME types is security-sensitive</div> <div> Security Hotspot</div>
<div>Disabling content security policy</div>