




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6


 XML





JavaScript static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code


All rules285

 Vulnerability29

 Bug62

 Security Hotspot43


 Code Smell151

 Quick Fix41

Tags


Search by name...

Return values from functions without side effects should not be ignored




Bug

Special identifiers should not be bound or assigned




Bug

Values should not be uselessly incremented




Bug

Related "if/else if" statements should not have the same condition




Bug

Objects should not be created to be dropped immediately without being used




Bug

Identical expressions should not be used on both sides of a binary operator




Bug

All code should be reachable




Bug

Loops with at most one iteration should be refactored




Bug

Variables should not be self-assigned




Bug

Function argument names should be unique




Bug

Property names should not be duplicated within a class or object literal



Bug

Bitwise operators should not be used



Bug

Using pseudorandom number generators (PRNGs) is security-sensitive

Security Hotspot

Critical

cwe owasp

Using pseudorandom number generators (PRNGs) is security-sensitive. For example, it has led in the past to the following vulnerabilities:

- CVE-2013-6386
- CVE-2006-3419
- CVE-2008-4102

When software generates predictable values in a context requiring unpredictability, it may be possible for an attacker to guess the next value that will be generated, and use this guess to impersonate another user or access sensitive information.

As the `Math.random()` function relies on a weak pseudorandom number generator, this function should not be used for security-critical applications or for protecting sensitive data. In such context, a cryptographically strong pseudorandom number generator (CSPRNG) should be used instead.

Ask Yourself Whether

- the code using the generated value requires it to be unpredictable. It is the case for all encryption mechanisms or when a secret value, such as a password, is hashed.
- the function you use generates a value which can be predicted (pseudorandom).
- the generated value is used multiple times.
- an attacker can access the generated value.

There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

- Use a cryptographically strong pseudorandom number generator (CSPRNG) like `crypto.getRandomValues()`.
- Use the generated random values only once.
- You should not expose the generated random value. If you have to store it, make sure that the database or file is secure.

Sensitive Code Example

```
const val = Math.random(); // Sensitive
// Check if val is used in a security context.
```





Compliant Solution

```
// === Client side ===
const crypto = window.crypto || window.msCrypto;
var array = new Uint32Array(1);
crypto.getRandomValues(array); // Compliant for security-sen

// === Server side ===
```

https://rules.sonarsource.com/javascript/RSPEC-2245

1/2

<div>Boolean operators should not be used in boolean contexts</div> <div> Bug</div>
<div>Constructing arguments of system commands from user input is security-sensitive</div> <div> Security Hotspot</div>
<div>Allowing requests with excessive content length is security-sensitive</div> <div> Security Hotspot</div>
<div>Statically serving hidden files is security-sensitive</div> <div> Security Hotspot</div>

```
const crypto = require('crypto');
const buf = crypto.randomBytes(1); // Compliant for security
```

See

- [OWASP Top 10 2021 Category A2](#) - Cryptographic Failures
- [OWASP Top 10 2017 Category A3](#) - Sensitive Data Exposure
- [Mobile AppSec Verification Standard](#) - Cryptography Requirements
- [OWASP Mobile Top 10 2016 Category M5](#) - Insufficient Cryptography
- [MITRE, CWE-338](#) - Use of Cryptographically Weak Pseudo-Random Number Generator (PRNG)
- [MITRE, CWE-330](#) - Use of Insufficiently Random Values
- [MITRE, CWE-326](#) - Inadequate Encryption Strength
- [MITRE, CWE-1241](#) - Use of Predictable Algorithm in Random Number Generator
- Derived from FindSecBugs rule [Predictable Pseudo Random Number Generator](#)

Available In:
 