




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51

Security Hotspot 43

Code Smell 158

Quick Fix 50

Tags ▾

Search by name... 🔍

Security Hotspot

Having a permissive Cross-Origin Resource Sharing policy is security-sensitive

Security Hotspot

Delivering code in production with debug features activated is security-sensitive

Security Hotspot

Creating cookies without the "HttpOnly" flag is security-sensitive

Security Hotspot

Creating cookies without the "secure" flag is security-sensitive

Security Hotspot

Using hardcoded IP addresses is security-sensitive

Security Hotspot

Regular expression quantifiers and character classes should be used concisely

Code Smell

Regular expression literals should be used when possible

Code Smell

"await" should not be used redundantly

Code Smell

Redundant casts and non-null assertions should be avoided

Code Smell

Type aliases should be used

Code Smell

Type guards should be used

Code Smell

Loops with at most one iteration should be refactored

Analyze your code

Bug

Major

A loop with at most one iteration is equivalent to the use of an `if` statement to conditionally execute one piece of code. No developer expects to find such a use of a loop statement. If the initial intention of the author was really to conditionally execute one piece of code, an `if` statement should be used instead.

At worst that was not the initial intention of the author and so the body of the loop should be fixed to use the nested `return`, `break` or `throw` statements in a more appropriate way.

Noncompliant Code Example

```
for (let i = 0; i < 10; i++) { // noncompliant, loop only ex
  console.log("i is " + i);
  break;
}
...
for (let i = 0; i < 10; i++) { // noncompliant, loop only ex
  if (i == x) {
    break;
  } else {
    console.log("i is " + i);
    return;
  }
}
```

Compliant Solution

```
for (let i = 0; i < 10; i++) {
  console.log("i is " + i);
}
...
for (let i = 0; i < 10; i++) {
  if (i == x) {
    break;
  } else {
    console.log("i is " + i);
  }
}
```





Available In:

sonarlint | sonarcloud | sonarqube

https://rules.sonarsource.com/typescript/RSPEC-1751

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of

1/2

"module" should not be used  Code Smell
"for of" should be used with Iterables  Code Smell
Imports from the same modules should be merged  Code Smell
Jump statements should not be redundant  Code Smell