

# STAYING SHARP

*with  
AngularJS*
















# Services Level 3

5 Recipes and a Factory Section 1



# Current State of Our App

- ✓  Note Wrangler
  -  index.html
  - ›  css
  - ✓  js
    -  app.js
  - ✓  controllers
    -  app.js
  - ›  filters
  - ›  directives
  - ›  templates





# Controllers Currently Have AJAX \$http Calls

notes-edit-controller.js

```
angular.module("NoteWrangler")
.controller("NotesEditController", function($scope, $http) {
  $scope.updateNote = function(noteObj) {
    $http({method: "PUT", url: "/notes", data: noteObj})
    ...
  }
});
```

This code is fine, but it's not reusable across other parts of our application. It is also going to be harder to test.

Where should this code be then?



# 🔌 A Service for Your Data

Services should hold functions responsible for connecting and fetching data, and then sharing it across our application.

## ✓ 📁 Note Wrangler

📄 index.html

› 📁 CSS

✓ 📁 js


📄 app.js

› 📁 controllers

› 📁 directives

› 📁 services

› 📁 templates





# 🔌 A Service for Your Data

Services should hold functions responsible for connecting and fetching data, and then sharing it across our application.

## ✓ 📁 Note Wrangler

📄 index.html

› 📁 CSS

✓ 📁 js


📄 app.js

› 📁 controllers

› 📁 directives

› 📁 services

› 📁 templates





# ⚡ Creating and Including the Service File

## ✓ 📁 Note Wrangler

📄 index.html

› 📁 css

✓ 📁 js

📄 app.js

› 📁 controllers

› 📁 directives

✓ 📁 services

📄 note.js

› 📁 templates

Create

📄 index.html

...

<ng-view>

<script src="vendor/jquery.js"></script>

<script src="vendor/angular.js"></script>

<script src="vendor/angular-route.js"></script>

<script src="/js/app.js"></script>

<script src="/js/routes.js"></script>

<!-- Services -->

<script src="/js/services/note.js"></script>

</body>

</html>

Include



# # 5 Service Recipes

We need to choose a recipe. There are 5 total recipes that range in complexity and customization. Factory and Provider are the two most commonly used for creating a Service.

- Value
  - Factory
  - Service
  - Provider
  - Constant
- 2 most common
- 
- A diagram consisting of two white arrows pointing from the text "2 most common" to the "Factory" and "Provider" items in the list above.



# # 2 Most Used Service Recipes

---

- Factory Most commonly used  
Used for sharing functions and objects across an application.
- Provider Commonly used  
Used for sharing methods and objects (like a Factory), but allows for configuration.





# ⚡ Creating a Service With the Factory Recipe

Use the Factory recipe to register the service with our app module.

services/note.js

```
angular.module("NoteWrangler")  
  .factory("Note", function NoteFactory() {  
    ...  
  });
```



Remember the  
naming convention  
<name> + <recipe>

Factory recipe



```
angular.module("<ModuleName>")  
  .factory("<ServiceName>", function <ServiceName>Factory() {  
    return { <object containing shared functions> }  
  });
```



# ⚡ Populating Our Factory Service

notes-index-controller.js

```
angular.module("NoteWrangler")
.controller("NotesIndexController", function($scope, $http) {
  $scope.notes = $http({method: "GET", url: "/notes"});
});
```

services/note.js



Service

all

create

Inside our factory service we'll define reusable methods that make our \$http calls.



# 🔧 Populating Our Factory Service

The all method gets a list of all the notes, and create posts a new note.

📄 services/note.js

```
angular.module("NoteWrangler")
.factory("Note", function NoteFactory() {
  return {
    all: function() {
      return $http({method: "GET", url: "/notes"});
    },
    create: function(note) {
      return $http({method: "POST", url: "/notes", data: note});
    }
  }
});
```



# # Calling Our Factory Service

services/note.js

```
angular.module("NoteWrangler")
.factory("Note", function NoteFactory() {
  return {
    all: function() { return $http({method: "GET", url: "/notes"}); },
    ...
  }
});
```

notes-index-controller.js

```
angular.module("NoteWrangler")
.controller("NotesIndexController", function($scope) {
  $http({method: "GET", url: "/notes"})
  .success(function(data) {
    $scope.notes = data;
  });
});
```



# 🔧 Calling Our Factory Service

Our notes controller now needs to use the notes factory.

📄 notes-index-controller.js

```
angular.module("NoteWrangler")
.controller("NotesIndexController", function($scope) {
  $http({method: "GET", url: "/notes"})
    .success(function(data) {
      $scope.notes = data;
    });
});
```




# # Injecting Factory Service

To use methods from the service, we need to first inject it into our controller.

notes-index-controller.js

```
angular.module("NoteWrangler")
.controller("NotesIndexController", function($scope, Note) {

    .success(function(data) {
        $scope.notes = data;
    });
});
```





# 🔧 Calling Our Factory Service

Now our controller has access to, and can call, the notes factory.

📄 notes-index-controller.js

```
angular.module("NoteWrangler")
.controller("NotesIndexController", function($scope, Note) {
  Note.all()
  .success(function(data) {
    $scope.notes = data;
  });
});
```

Notice **Note** has no \$. The \$ prefix is reserved for built-in Angular services.