




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

- All rules 285
- Vulnerability 29
- Bug 62
- Security Hotspot 43
- Code Smell 151
- Quick Fix 41

Assignments should not be redundant
Code Smell
Functions should not have identical implementations
Code Smell
Sparse arrays should not be declared
Code Smell
Array-mutating methods should not be used misleadingly
Code Smell
Collection and array contents should be used
Code Smell
Functions should always return the same type
Code Smell
Arguments to built-in functions should match documented types
Code Smell
Literals should not be thrown
Code Smell
Functions should not be called both with and without "new"
Code Smell
Array indexes should be numeric
Code Smell
Assertion arguments should be passed in the correct order
Code Smell
Ternary operators should not be nested
Code Smell

Alternation in regular expressions should not contain empty alternatives

Analyze your code

Bug

Major

regex

Alternation is used to match a single regular expression out of several possible regular expressions. If one of the alternatives is empty it would match any input, which is most probably a mistake.

Noncompliant Code Example

```
/Jack|Peter|/.test('John'); // Noncompliant - returns 'true'
/Jack|Peter/.test('John'); // Noncompliant - returns 'true'
```

Compliant Solution

```
/Jack|Peter/.test('John'); // returns 'false'
```

Exceptions

One could use an empty alternation to make a regular expression group optional. Rule will not report on such cases.





```
/mandatory(-optional|)/.test('mandatory'); // returns 'true'
/mandatory(-optional|)/.test('mandatory-optional'); // returns 'true'
```

However, if there is a quantifier after the group the issue will be reported as using both | and quantifier is redundant.

```
/mandatory(-optional|)?/.test('mandatory'); // Noncompliant
```

Available In:

sonarlint | sonarcloud | sonarqube

<div>"delete" should not be used on arrays</div> <div> Code Smell</div>
<div>Variables and functions should not be redeclared</div> <div> Code Smell</div>
<div>"indexOf" checks should not be for positive numbers</div> <div> Code Smell</div>
<div>"arguments.caller" and "arguments.callee" should not be used</div> <div> Code Smell</div>