




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 **JavaScript**


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

All rules 285

 Vulnerability 29

 Bug 62











 Security Hotspot 43

 Code Smell 151

 Quick Fix 41

Tags ▾

Search by name... 🔍

Disabling content security policy fetch directives is security-sensitive		Security Hotspot
Disabling resource integrity features is security-sensitive		Security Hotspot
Disclosing fingerprints from web application technologies is security-sensitive		Security Hotspot
Having a permissive Cross-Origin Resource Sharing policy is security-sensitive		Security Hotspot
Delivering code in production with debug features activated is security-sensitive		Security Hotspot
Creating cookies without the "HttpOnly" flag is security-sensitive		Security Hotspot
Creating cookies without the "secure" flag is security-sensitive		Security Hotspot
Using hardcoded IP addresses is security-sensitive		Security Hotspot
Regular expression quantifiers and character classes should be used concisely		Code Smell
Regular expression literals should be used when possible		Code Smell
"await" should not be used redundantly		

Loops with at most one iteration should be refactored

Analyze your code

 Bug

 Major



A loop with at most one iteration is equivalent to the use of an `if` statement to conditionally execute one piece of code. No developer expects to find such a use of a loop statement. If the initial intention of the author was really to conditionally execute one piece of code, an `if` statement should be used instead.

At worst that was not the initial intention of the author and so the body of the loop should be fixed to use the nested `return`, `break` or `throw` statements in a more appropriate way.

Noncompliant Code Example






```
for (let i = 0; i < 10; i++) { // noncompliant, loop only ex
  console.log("i is " + i);
  break;
}
...
for (let i = 0; i < 10; i++) { // noncompliant, loop only ex
  if (i == x) {
    break;
  } else {
    console.log("i is " + i);
    return;
  }
}
```

Compliant Solution

```
for (let i = 0; i < 10; i++) {
  console.log("i is " + i);
}
...
for (let i = 0; i < 10; i++) {
  if (i == x) {
    break;
  } else {
    console.log("i is " + i);
  }
}
```

Available In:

 |  | 

 Code Smell
"for of" should be used with Iterables  Code Smell
Imports from the same modules should be merged  Code Smell
Jump statements should not be redundant  Code Smell
Default export names and file names should match  Code Smell

SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)