




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 **JavaScript**


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML














JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

- All rules** 285
-  Vulnerability 29
-  Bug 62
-  Security Hotspot 43
-  Code Smell 151
-  Quick Fix 41




Tags ▾

Search by name... 🔍

Regular expressions with the global flag should be used with caution	
Replacement strings should reference existing regular expression groups	
Regular expressions should not contain control characters	
Alternation in regular expressions should not contain empty alternatives	
Mocha timeout should be disabled by setting it to "0".	
Unicode Grapheme Clusters should be avoided inside regex character classes	
Assertions should not be given twice the same argument	
Alternatives in regular expressions should be grouped when used with anchors	
Promise rejections should not be caught by 'try' block	
Collection elements should not be replaced unconditionally	
Errors should not be created without being thrown	

Function calls should not pass extra arguments

Analyze your code

 Bug  Critical  cwe

You can easily call a JavaScript function with more arguments than the function needs, but the extra arguments will be just ignored by function execution.

Noncompliant Code Example

```
function say(a, b) {
  print(a + " " + b);
}

say("hello", "world", "!"); // Noncompliant; last argument is extra
```

Exceptions

No issue is reported when arguments is used in the body of the function being called.

```
function doSomething(a, b) {
  compute(arguments);
}

doSomething(1, 2, 3) // Compliant
```





See

- [MITRE, CWE-628](#) - Function Call with Incorrectly Specified Arguments

Available In:

sonarlint  | **sonarcloud**  | **sonarqube** 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. [Privacy Policy](#)

<p>Collection sizes and array length comparisons should make sense</p> <p> Bug</p>
<p>All branches in a conditional structure should not have exactly the same implementation</p> <p> Bug</p>
<p>Destructuring patterns should not be empty</p> <p> Bug</p>
<p>The output of functions that don't return anything should not be used</p> <p> Bug</p>