


# Traversing and Filtering



How do we allow vacations to have different prices?



# Tackling the HTML

#### index.html

```
    <h3>Hawaiian Vacation</h3>
    <button>Get Price</button>

        Amazing deal!
        Want to go!

All data attributes begin with 'data-'
```

```
$('.vacation').first().data('price');
"399.99"
```

```
jQuery Object Methods
```

```
.data(<name>)
```

## Refactoring 'Get Price'

```
$ application.js

$ (document).ready(function() {
    $ ('button').on('click', function() {
       var price = $ ('From $399.99');
       $ (this).closest('.vacation').append(price);
       $ (this).remove();
       });
    });

Reads from the data-price attribute
```

```
var amount = $(this).closest('.vacation').data('price');
var price = $('From $'+amount+'');
```

Joins two strings to create the price



### Refactoring 'Get Price'

application.js

```
$(document).ready(function() {
    $('button').on('click', function() {
       var amount = $(this).closest('.vacation').data('price');
       var price = $('From $'+amount+'');
       $(this).closest('.vacation').append(price);
       $(this).remove();
    });
       Each vacation can have its own price
```

### Reusing jQuery Objects

```
application.js
```


```
$(document).ready(function() {
    $('button').on('click', function() {
       var amount = $(this).closest('.vacation').data('price');
       var price = $('From $'+amount+'');
    $(this).closest('.vacation').append(price);
    $(this).remove();
    });
});
```

```
var vacation = $(this).closest('.vacation');
var amount = vacation.data('price');
vacation.append(price);
```

#### Reusing jQuery Objects

#### application.js

```
$(document).ready(function() {
  $('button').on('click', function() {
    var vacation = $(this).closest('.vacation');
    var amount = vacation.data('price');
     var price = $('From $'+amount+'');
    vacation.append(price);
    $(this).remove();
 });
                              We'll only query the DOM
});
                              once for this element
```




Each vacation can have its dynamic own price now



#### On With a Selector

```
application.js
$(document).ready(function() {
  $('button').on('click', function() {
 });
});
              If we add new buttons anywhere, they will trigger this click handler
$('.vacation button').on('click', function() {});
$('.vacation').on('click', 'button', function() {});
                                                  Only target a 'button'
                                                  if it's inside a '.vacation'
```



### Filtering HTML

#### index.html

```
<div id='filters'>
...
    <button class='onsale-filter'>On Sale Now</button>
        <button class='expiring-filter'>Expiring</button>
...
</div>
```

We'll write 2 event handlers for our buttons

We'll highlight vacations with these traits

```
DOCUMENT


div id="filters"

button class="onsale-filter"

button class="expiring-filter"
```

});

```
application.js
$('#filters').on('click', '.onsale-filter',
                    function() {
    find all vacations that are on-sale
  // add a class to these vacations
});
$('.vacation.onsale')
$('.vacation').filter('.onsale')
                       Finds elements with a class
                       of .vacation and .onsale
```



#### **Class Manipulation**

```
.addClass(<class>)
```



.removeClass(<class>)

```
DOCUMENT
       class="vacation onsale"
             class="comments"
        class="vacation"
        class="vacation"
```

```
$('.vacation').filter('.onsale').addClass('highlighted');
```




#### application.js

```
$('#filters').on('click', '.onsale-filter', function() {
   $('.vacation').filter('.onsale').addClass('highlighted');
});
Finds only the right vacations
Adds a class of 'highlighted'
```

The same can be done for our **expiring** filter

```
$('#filters').on('click', '.expiring-filter', function() {
   $('.vacation').filter('.expiring').addClass('highlighted');
});
```



How do we make sure not all vacations are highlighted?




### Unhighlighting Vacations

```
application.js
```

```
$('#filters').on('click', '.onsale-filter', function() {
   $('.highlighted').removeClass('highlighted');
   $('.vacation').filter( .onsale').addClass('highlighted');
});
```

Remove the highlighted class before adding it back



We clear the highlighted class on click, only highlighting the targeted vacations

