




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



## TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules279

Vulnerability27

Bug51

Security Hotspot43

Code Smell158

Quick Fix50

Tags ▾

Search by name... 🔍

Empty collections should not be accessed or iterated

Bug

"delete" should be used only with object properties

Bug

Function parameters, caught exceptions and foreach variables' initial values should not be ignored

Bug

Forwarding client IP address is security-sensitive

Security Hotspot

Allowing confidential information to be logged is security-sensitive

Security Hotspot

Allowing browsers to perform DNS prefetching is security-sensitive

Security Hotspot

Disabling Certificate Transparency monitoring is security-sensitive

Security Hotspot

Disabling Strict-Transport-Security policy is security-sensitive

Security Hotspot

Disabling strict HTTP no-referrer policy is security-sensitive

Security Hotspot

Allowing browsers to sniff MIME types is security-sensitive

Security Hotspot

Disabling content security policy frame-ancestors directive is security-sensitive

Security Hotspot

### A "for" loop update clause should move the counter in the right direction

Analyze your code

BugMajor?

A `for` loop with a stop condition that can never be reached, such as one with a counter that moves in the wrong direction, will run infinitely. While there are occasions when an infinite loop is intended, the convention is to construct such loops as `while` loops. More typically, an infinite `for` loop is a bug.

#### Noncompliant Code Example

```
for (var i = 0; i < strings.length; i--) { // Noncompliant;
  //...
}
```

#### Compliant Solution

```
for (var i = 0; i < strings.length; i++) {
  //...
}
```

Available In:





sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-2251

1/2

<div>Allowing mixed-content is security-sensitive</div> <div> Security Hotspot</div>
<div>Disabling content security policy fetch directives is security-sensitive</div> <div> Security Hotspot</div>
<div>Disabling resource integrity features is security-sensitive</div> <div> Security Hotspot</div>
<div>Disclosing fingerprints from web application technologies is security-sensitive</div> <div> Security Hotspot</div>