




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

- All rules 285
- Vulnerability 29
- Bug 62
- Security Hotspot 43
- Code Smell 151
- Quick Fix 41

Security Hotspot
Using shell interpreter when executing OS commands is security-sensitive
Security Hotspot
Setting loose POSIX file permissions is security-sensitive
Security Hotspot
Formatting SQL queries is security-sensitive
Security Hotspot
Comma operator should not be used
Code Smell
Regular expressions should not contain empty groups
Code Smell
Regular expressions should not contain multiple spaces
Code Smell
Chai assertions should have only one reason to succeed
Code Smell
Single-character alternations in regular expressions should be replaced with character classes
Code Smell
Reluctant quantifiers in regular expressions should be followed by an expression that can't match the empty string
Code Smell
Tests should check which exception is thrown
Code Smell
Character classes in regular expressions should not contain the

Tags ▾

Search by name... 🔍

"void" should not be used

Analyze your code

- Code Smell
- Critical
- confusing

The `void` operator evaluates its argument and unconditionally returns `undefined`. It can be useful in pre-ECMAScript 5 environments, where `undefined` could be reassigned, but generally, its use makes code harder to understand.

Noncompliant Code Example

```
void doSomething();
```

Compliant Solution

```
doSomething();
```

Exceptions

No issue is raised when `void 0` is used in place of `undefined`.

```
if (parameter === void 0) {...}
```

No issue is raised when `void` is used before immediately invoked function expressions.





```
void (function() {  
  ...  
})();
```

No issue is raised when `void`'s argument is a promise.

```
const promise = new Promise((resolve, reject) => {  
  setTimeout(() => {  
    resolve('done');  
  }, 3000);  
});  
void promise;
```

Available In:

sonarlint | sonarcloud | sonarqube

<div>same character twice</div> <div> Code Smell</div>
<div>Names of regular expressions named groups should be used</div> <div> Code Smell</div>
<div>Regular expressions should not be too complicated</div> <div> Code Smell</div>
<div>Shorthand promises should be used</div> <div> Code Smell</div>
<div>Template literals should not be nested</div>