




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6


 XML





TypeScript static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code


All rules279

 Vulnerability27

 Bug51


 Security Hotspot43

 Code Smell158


 Quick Fix50

Tags ▾


Search by name... 🔍

 Code Smell


Primitive types should be omitted from initialized or defaulted declarations




Non-null assertions should not be used




"undefined" should not be assigned




Trailing commas should not be used




Array constructors should not be used




Quotes for string literals should be used consistently




Statements should end with semicolons




Comments should not be located at the end of lines of code




Loops should not contain more than a single "break" or "continue" statement



Variable, property and parameter names should comply with a naming convention






Lines should not end with trailing whitespaces



Track uses of "TODO" tags

Analyze your code

 Code Smell  Info  cwe

TODO tags are commonly used to mark places where some more code is required, but which the developer wants to implement later.

Sometimes the developer will not have the time or will simply forget to get back to that tag.

This rule is meant to track those tags and to ensure that they do not go unnoticed.




Noncompliant Code Example

```
function doSomething() {  
  // TODO  
}
```

See

- [MITRE, CWE-546](#) - Suspicious Comment

Available In:

 |  | 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-1135

1/2

<div>Files should contain an empty newline at the end</div> <div> Code Smell</div>
<div>An open curly brace should be located at the end of a line</div> <div> Code Smell</div>
<div>Tabulation characters should not be used</div> <div> Code Smell</div>
<div>Function and method names should comply with a naming convention</div> <div> Code Smell</div>