




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text

 TypeScript

 T-SQL

 VB.NET

 VB6

 XML















JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

- All rules 285
- Vulnerability 29
- Bug 62
- Security Hotspot 43
- Code Smell 151
- Quick Fix 41

Tags ▾

Search by name... 🔍

 Bug
Promise rejections should not be caught by 'try' block
 Bug
Collection elements should not be replaced unconditionally
 Bug
Errors should not be created without being thrown
 Bug
Collection sizes and array length comparisons should make sense
 Bug
All branches in a conditional structure should not have exactly the same implementation
 Bug
Destructuring patterns should not be empty
 Bug
The output of functions that don't return anything should not be used
 Bug
Comma and logical OR operators should not be used in switch cases
 Bug
Generators should "yield" something
 Bug
Attempts should not be made to update "const" variables
 Bug
Strict equality operators should not be used with dissimilar types
 Bug

"in" should not be used with primitive types

Analyze your code

 Bug  Critical ?

The `in` operator tests whether the specified property is in the specified object.

If the right operand is a of primitive type (i.e., not an object) the `in` operator raises a `TypeError`.

Noncompliant Code Example

```
var x = "Foo";
"length" in x; // Noncompliant: TypeError
0 in x;        // Noncompliant: TypeError
```

Compliant Solution






```
var x = new String("Foo");
"length" in x;    // true
0 in x;           // true
"foobar" in x;    // false
```

Available In:

sonarlint  | sonarcloud  | sonarqube 

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

<div><div>"new" operators should be used with functions</div><div> Bug</div></div>
<div><div>Non-existent operators '+=', '=-' and '!=' should not be used</div><div> Bug</div></div>
<div><div>"NaN" should not be used in comparisons</div><div> Bug</div></div>
<div><div>Setters should not return values</div><div> Bug</div></div>
<div><div>Division of finite by zero "0/0"</div><div> Bug</div></div>