




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6


 XML





TypeScript static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code


All rules 279

 Vulnerability 27


 Bug 51

 Security Hotspot 43


 Code Smell 158

 Quick Fix 50

Tags ▾


Search by name... 

The global "this" object should not be used




Code Smell

"catch" clauses should do more than rethrow




Code Smell

Boolean checks should not be inverted




Code Smell

Deprecated APIs should not be used




Code Smell

Wrapper objects should not be used for primitive types




Code Smell

Multiline string literals should not be used




Code Smell

Local variables should not be declared and then immediately returned or thrown




Code Smell

Function call arguments should not start on new lines




Code Smell

"switch" statements should have at least 3 "case" clauses




Code Smell

A "while" loop should be used instead of a "for" loop




Code Smell

Unnecessary imports should be removed



Code Smell




Boolean literals should not be used in comparisons



Code Smell

Setting loose POSIX file permissions is security-sensitive

Analyze your code

 Security Hotspot  Major  cwe sans-top25 owasp

In Unix, "others" class refers to all users except the owner of the file and the members of the group assigned to this file.

Granting permissions to this group can lead to unintended access to files.

Ask Yourself Whether

- The application is designed to be run on a multi-user environment.
- Corresponding files and directories may contain confidential information.

There is a risk if you answered yes to any of those questions.

Recommended Secure Coding Practices

The most restrictive possible permissions should be assigned to files and directories.

Sensitive Code Example

Node.js **fs**

```
const fs = require('fs');

fs.chmodSync("/tmp/fs", 0o777); // Sensitive
```

const fs = require('fs');
const fsPromises = fs.promises;

fsPromises.chmod("/tmp/fsPromises", 0o777); // Sensitive

```
const fs = require('fs');
const fsPromises = fs.promises






async function fileHandler() {
  let filehandle;
  try {
    filehandle = fsPromises.open('/tmp/fsPromises', 'r');
    filehandle.chmod(0o777); // Sensitive
  } finally {
    if (filehandle !== undefined)
      filehandle.close();
  }
}
```

Node.js **process.umask**

```
const process = require('process');
```

https://rules.sonarsource.com/typescript/RSPEC-2612

1/2

 Code Smell
Extra semicolons should be removed
 Code Smell
Class names should comply with a naming convention
 Code Smell
Track uses of "TODO" tags
 Code Smell
Web SQL databases should not be used
 Vulnerability

```
process.umask(0o000); // Sensitive
```

Compliant Solution

Node.js [fs](#)

```
const fs = require('fs');

fs.chmodSync("/tmp/fs", 0o770); // Compliant
```

```
const fs = require('fs');
const fsPromises = fs.promises;

fsPromises.chmod("/tmp/fsPromises", 0o770); // Compliant
```

```
const fs = require('fs');
const fsPromises = fs.promises

async function fileHandler() {
  let filehandle;
  try {
    filehandle = fsPromises.open('/tmp/fsPromises', 'r');
    filehandle.chmod(0o770); // Compliant
  } finally {
    if (filehandle !== undefined)
      filehandle.close();
  }
}
```

Node.js [process.umask](#)

```
const process = require('process');

process.umask(0o007); // Compliant
```

See

- [OWASP Top 10 2021 Category A1](#) - Broken Access Control
- [OWASP Top 10 2021 Category A4](#) - Insecure Design
- [OWASP Top 10 2017 Category A5](#) - Broken Access Control
- [OWASP File Permission](#)
- [MITRE, CWE-732](#) - Incorrect Permission Assignment for Critical Resource
- [MITRE, CWE-266](#) - Incorrect Privilege Assignment
- [SANS Top 25](#) - Porous Defenses

Available In:

sonarcloud  **sonarqube** 