

































-  Secrets
-  ABAP
-  Apex
-  C
-  C++
-  CloudFormation
-  COBOL
-  C#
-  CSS
-  Flex
-  Go
-  HTML
-  Java
-  JavaScript
-  Kotlin
-  Objective C
-  PHP
-  PL/I
-  PL/SQL
-  Python
-  RPG
-  Ruby
-  Scala
-  Swift
-  Terraform
-  Text
-  **TypeScript**
-  T-SQL
-  VB.NET
-  VB6
-  XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules279

Vulnerability27

Bug51

Security Hotspot43

Code Smell158

Quick Fix50

Tags

Search by name...

Results of "in" and "instanceof" should be negated rather than operands

Bug

A compare function should be provided when using "Array.prototype.sort()"

Bug

Jump statements should not occur in "finally" blocks

Bug

Using slow regular expressions is security-sensitive

Security Hotspot

Using publicly writable directories is security-sensitive

Security Hotspot

Using clear-text protocols is security-sensitive

Security Hotspot

Expanding archive files without controlling resource consumption is security-sensitive

Security Hotspot

Using weak hashing algorithms is security-sensitive

Security Hotspot

Disabling CSRF protections is security-sensitive

Security Hotspot

Using pseudorandom number generators (PRNGs) is security-sensitive

Security Hotspot

Dynamically executing code is security-sensitive

Security Hotspot

Switch cases should end with an unconditional "break" statement

Analyze your code

Code Smell

Blocker

cwe suspicious

When the execution is not explicitly terminated at the end of a switch case, it continues to execute the statements of the following case. While this is sometimes intentional, it often is a mistake which leads to unexpected behavior.

Noncompliant Code Example

```
switch (myVariable) {
  case 1:
    foo();
    break;
  case 2: // Both 'doSomething()' and 'doSomethingElse()' w
    doSomething();
  default:
    doSomethingElse();
    break;
}
```





Compliant Solution

```
switch (myVariable) {
  case 1:
    foo();
    break;
  case 2:
    doSomething();
    break;
  default:
    doSomethingElse();
    break;
}
```

Exceptions

This rule is relaxed in the following cases:

```
switch (myVariable) {
  case 0: // Empty case used
  case 1:
    doSomething();
    break;
  case 2: // Use of return st
    return;
  case 3: // Ends with comment
    console.log("this case falls through")
    // fall through
  case 4: // Use of throw sta
    throw new IllegalStateException();
  case 5: // Use of continue
```

<p>Equality operators should not be used in "for" loop termination conditions</p> <p> Code Smell</p>
<p>Tests should not execute any code after "done()" is called</p> <p> Code Smell</p>
<p>Union and intersection types should not be defined with duplicated elements</p> <p> Code Smell</p>
<p>"default" clauses should be last</p> <p> Code Smell</p>

```
    continue;
    default:                                     // For the last cas
        doSomethingElse();
}
```

See

- [MITRE, CWE-484](#) - Omitted Break Statement in Switch

Available In:

sonarlint

|

sonarcloud

|

sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)