




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51

Security Hotspot 43

Code Smell 158

Quick Fix 50

Tags ▾

Search by name... 🔍

Literals should not be thrown

Code Smell

Array indexes should be numeric

Code Smell

Assertion arguments should be passed in the correct order

Code Smell

Ternary operators should not be nested

Code Smell

"delete" should not be used on arrays

Code Smell

Variables and functions should not be redeclared

Code Smell

"indexOf" checks should not be for positive numbers

Code Smell

"arguments.caller" and "arguments.callee" should not be used

Code Smell

Multiline blocks should be enclosed in curly braces

Code Smell

Boolean expressions should not be gratuitous

Code Smell

Variables should be used in the blocks where they are declared

Code Smell

Parameters should be passed in the correct order

Code Smell

Unicode Grapheme Clusters should be avoided inside regex character classes

Bug

Major

regex

Analyze your code

When placing Unicode **Grapheme Clusters** (characters which require to be encoded in multiple **Code Points**) inside a character class of a regular expression, this will likely lead to unintended behavior.

For instance, the grapheme cluster **ö** requires two code points: one for 'c', followed by one for the *umlaut* modifier '\u{0308}'. If placed within a character class, such as [**ö**], the regex will consider the character class being the enumeration [c\u{0308}] instead. It will, therefore, match every 'c' and every *umlaut* that isn't expressed as a single codepoint, which is extremely unlikely to be the intended behavior.

This rule raises an issue every time Unicode Grapheme Clusters are used within a character class of a regular expression.

Noncompliant Code Example

```
"cödd".replace(/[ö]/g, "x"); // result is "XXXXXX" and not
```

Compliant Solution

```
"cödd".replace(/ö|ä/g, "x"); // result is "cXXd"
```

Available In:

sonarlint

sonarcloud





sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-5868

1/2

<div>Two branches in a conditional structure should not have exactly the same implementation</div> <div> Code Smell</div>
<div>Unused assignments should be removed</div> <div> Code Smell</div>
<div>Function parameters with default values should be last</div> <div> Code Smell</div>
<div>Functions should not be defined inside loops</div> <div></div>