




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6

 XML



TypeScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code

All rules 279

Vulnerability 27

Bug 51

Security Hotspot 43

Code Smell 158

Quick Fix 50

Tags ▾

Search by name... 🔍

Variables should not be self-assigned

Bug

Bitwise operators should not be used in boolean contexts

Bug

Constructing arguments of system commands from user input is security-sensitive

Security Hotspot

Allowing requests with excessive content length is security-sensitive

Security Hotspot

Statically serving hidden files is security-sensitive

Security Hotspot

Using intrusive permissions is security-sensitive

Security Hotspot

Disabling auto-escaping in template engines is security-sensitive

Security Hotspot

Using shell interpreter when executing OS commands is security-sensitive

Security Hotspot

Setting loose POSIX file permissions is security-sensitive

Security Hotspot

Formatting SQL queries is security-sensitive

Security Hotspot

Comma operator should not be used

Code Smell

Regular expressions should not contain empty groups

Code Smell

"await" should only be used with promises

Analyze your code

Code Smell

Critical

confusing

It is possible to use await on values which are not Promises, but it's useless and misleading. The point of await is to pause execution until the Promise's asynchronous code has run to completion. With anything other than a Promise, there's nothing to wait for.

This rule raises an issue when an awaited value is guaranteed not to be a Promise.

Noncompliant Code Example

```
let x = 42;
await x; // Noncompliant
```

Compliant Solution

```
let x = new Promise(resolve => resolve(42));
await x;

let y = p ? 42 : new Promise(resolve => resolve(42));
await y;
```





Available In:

sonarlint | sonarcloud | sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)

https://rules.sonarsource.com/typescript/RSPEC-4123

1/2

 Code Smell
<div>Regular expressions should not contain multiple spaces</div> <div> Code Smell</div>
<div>Chai assertions should have only one reason to succeed</div> <div> Code Smell</div>
<div>Single-character alternations in regular expressions should be replaced with character classes</div> <div> Code Smell</div>
<div>Reluctant quantifiers in regular expressions should be followed by an expression that can't match the empty</div>