




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 **JavaScript**


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 TypeScript

 T-SQL

 VB.NET

 VB6

 XML



JavaScript static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your JAVASCRIPT code

All rules 285

Vulnerability 29

Bug 62

Security Hotspot 43

Code Smell 151

Quick Fix 41

Tags ▾

Search by name... 🔍

Assignments should not be made from within sub-expressions

Code Smell

Labels should not be used

Code Smell

Variables should not be shadowed

Code Smell

Redundant pairs of parentheses should be removed

Code Smell

Nested blocks of code should not be left empty

Code Smell

Functions should not have too many parameters

Code Smell

OS commands should not be vulnerable to argument injection attacks

Vulnerability

Repeated patterns in regular expressions should not match the empty string

Bug

Empty collections should not be accessed or iterated

Bug

"delete" should be used only with object properties

Bug

"with" statements should not be used

Bug

Function parameters, caught exceptions and foreach variables'

Strict equality operators should not be used with dissimilar types

Analyze your code

Bug

Major

Quick Fix

Comparing dissimilar types using the strict equality operators `===` and `!==` will always return the same value, respectively `false` and `true`, because no type conversion is done before the comparison. Thus, such comparisons can only be bugs.

Noncompliant Code Example

```
var a = 8;
var b = "8";

if (a === b) { // Noncompliant; always false
  // ...
}
```

Compliant Solution

```
var a = 8;
var b = "8";

if (a == b) {
  // ...
}
```

or

```
var a = 8;
var b = "8";

if (a === Number(b)) {
  // ...
}
```

Available In:

sonarlint

sonarcloud





sonarqube

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.

[Privacy Policy](#)

https://rules.sonarsource.com/javascript/RSPEC-3403

1/2

initial values should not be ignored  Bug
Forwarding client IP address is security-sensitive  Security Hotspot
Allowing confidential information to be logged is security-sensitive  Security Hotspot
Allowing browsers to perform DNS prefetching is security-sensitive  Security Hotspot
Disabling Certificate Transparency