




 Secrets


 ABAP


 Apex


 C


 C++


 CloudFormation


 COBOL


 C#


 CSS


 Flex


 Go


 HTML


 Java


 JavaScript


 Kotlin


 Objective C


 PHP


 PL/I


 PL/SQL


 Python


 RPG


 Ruby


 Scala


 Swift


 Terraform


 Text


 **TypeScript**

 T-SQL

 VB.NET

 VB6


 XML





## TypeScript static code analysis


Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your TYPESCRIPT code


All rules279

 Vulnerability27

 Bug51


 Security Hotspot43

 Code Smell158


 Quick Fix50

Tags


Search by name...

 Code Smell


Primitive types should be omitted from initialized or defaulted declarations




Non-null assertions should not be used




"undefined" should not be assigned




Trailing commas should not be used




Array constructors should not be used




Quotes for string literals should be used consistently




Statements should end with semicolons




Comments should not be located at the end of lines of code




Loops should not contain more than a single "break" or "continue" statement






Variable, property and parameter names should comply with a naming convention



Lines should not end with trailing whitespaces



### OS commands should not be vulnerable to argument injection attacks

 Vulnerability Minor injection cwe owasp sans-top25

Applications that allow execution of operating system commands from user-controlled data should control the arguments passed to the command, otherwise an attacker can inject additional arbitrary arguments which can change the behavior of the command.

User-controlled arguments should be sanitized by neutralizing argument delimiters (eg: ' , space, -) and thus preventing injection of unwanted additional arguments. A single user-controlled argument may still lead to vulnerabilities if it corresponds to a dangerous option supported by the command, such as -exec available with **find**, in that case, mark end of option processing on the command line using -- (double-dash) or restrict the options to only trusted values.

#### Noncompliant Code Example

When using the **execa** command function, arguments are defined next to the command as a string which can lead to arguments injection:

```
const execa = require('execa');

async function (req, res) {
  const cmd = "ls -la "+req.query.arg;

  const {stdout} = await execa.command(cmd); // Noncompliant
};
```

#### Compliant Solution

Prefer the execa function where the list of command arguments are defined as elements of an array:

```
const execa = require('execa');


async function (req, res) {
  const arg = req.query.arg;

  const {stdout} = await execa("ls", ["-la", arg]); // Compliant
};
```

#### See






- [OWASP Top 10 2021 Category A3](#) - Injection
- OWASP OS Command Injection Defense [Cheat Sheet](#)
- [OWASP Top 10 2017 Category A1](#) - Injection
- [MITRE, CWE-20](#) - Improper Input Validation
- [MITRE, CWE-88](#) - Argument Injection or Modification
- [SANS Top 25](#) - Insecure Interaction Between Components

Available In:

 Developer

https://rules.sonarsource.com/typescript/RSPEC-5883

1/2

<div>Files should contain an empty newline at the end</div> <div> Code Smell</div>	<div>sonarcloud   sonarqube  Edition</div> <div>© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved. <a href="#">Privacy Policy</a></div>
<div>An open curly brace should be located at the end of a line</div> <div> Code Smell</div>	
<div>Tabulation characters should not be used</div> <div> Code Smell</div>	
<div>Function and method names should comply with a naming convention</div> <div> Code Smell</div>	