

Kubernetes Components


A Kubernetes cluster consists of the components that are a part of the control plane and a set of machines called nodes.

When you deploy Kubernetes, you get a cluster.

A Kubernetes cluster consists of a set of worker machines, called nodes, that run containerized applications. Every cluster has at least one worker node.

The worker node(s) host the Pods that are the components of the application workload. The control plane manages the worker nodes and the Pods in the cluster. In production environments, the control plane usually runs across multiple computers and a cluster usually runs multiple nodes, providing fault-tolerance and high availability.

This document outlines the various components you need to have for a complete and working Kubernetes cluster.



The components of a Kubernetes cluster

Control Plane Components

The control plane's components make global decisions about the cluster (for example, scheduling), as well as detecting and responding to cluster events (for example, starting up a new pod when a deployment's `replicas` field is unsatisfied).

Control plane components can be run on any machine in the cluster. However, for simplicity, set up scripts typically start all control plane components on the same machine, and do not run user containers on this machine. See [Creating Highly Available clusters with kubeadm](#) for an example control plane setup that runs across multiple machines.

kube-apiserver

The API server is a component of the Kubernetes control plane that exposes the Kubernetes API. The API server is the front end for the Kubernetes control plane.

The main implementation of a Kubernetes API server is [kube-apiserver](#). kube-apiserver is designed to scale horizontally—that is, it scales by deploying more instances. You can run several instances of kube-apiserver and balance traffic between those instances.

etcd

Consistent and highly-available key value store used as Kubernetes' backing store for all cluster data.

If your Kubernetes cluster uses etcd as its backing store, make sure you have a [back up](#) plan for the data.

You can find in-depth information about etcd in the official [documentation](#).

kube-scheduler

Control plane component that watches for newly created Pods with no assigned node, and selects a node for them to run on.

Factors taken into account for scheduling decisions include: individual and collective resource requirements, hardware/software/policy constraints, affinity and anti-affinity specifications, data locality, inter-workload interference, and deadlines.

kube-controller-manager

Control plane component that runs controller processes.

Logically, each controller is a separate process, but to reduce complexity, they are all compiled into a single binary and run in a single process.

Some types of these controllers are:

- Node controller: Responsible for noticing and responding when nodes go down.
- Job controller: Watches for Job objects that represent one-off tasks, then creates Pods to run those tasks to completion.
- EndpointSlice controller: Populates EndpointSlice objects (to provide a link between Services and Pods).
- ServiceAccount controller: Create default ServiceAccounts for new namespaces.

cloud-controller-manager

A Kubernetes control plane component that embeds cloud-specific control logic. The cloud controller manager lets you link your cluster into your cloud provider's API, and separates out the components that interact with that cloud platform from components that only interact with your cluster.

The cloud-controller-manager only runs controllers that are specific to your cloud provider. If you are running Kubernetes on your own premises, or in a learning environment inside your own PC, the cluster does not have a cloud controller manager.

As with the kube-controller-manager, the cloud-controller-manager combines several logically independent control loops into a single binary that you run as a single process. You can scale horizontally (run more than one copy) to improve performance or to help tolerate failures.

The following controllers can have cloud provider dependencies:

- Node controller: For checking the cloud provider to determine if a node has been deleted in the cloud after it stops responding
- Route controller: For setting up routes in the underlying cloud infrastructure
- Service controller: For creating, updating and deleting cloud provider load balancers

Node Components

Node components run on every node, maintaining running pods and providing the Kubernetes runtime environment.

kubelet

An agent that runs on each node in the cluster. It makes sure that containers are running in a Pod.

The kubelet takes a set of PodSpecs that are provided through various mechanisms and ensures that the containers described in those PodSpecs are running and healthy. The kubelet doesn't manage containers which were not created by Kubernetes.

kube-proxy

kube-proxy is a network proxy that runs on each node in your cluster, implementing part of the Kubernetes Service concept.

[kube-proxy](#) maintains network rules on nodes. These network rules allow network communication to your Pods from network sessions inside or outside of your cluster.

kube-proxy uses the operating system packet filtering layer if there is one and it's available. Otherwise, kube-proxy forwards the traffic itself.

Container runtime

The container runtime is the software that is responsible for running containers.

Kubernetes supports container runtimes such as containerd, CRI-O, and any other implementation of the [Kubernetes CRI \(Container Runtime Interface\)](#).

Addons

Addons use Kubernetes resources (DaemonSet, Deployment, etc) to implement cluster features. Because these are providing cluster-level features, namespaced resources for addons belong within the `kube-system` namespace.

Selected addons are described below; for an extended list of available addons, please see [Addons](#).

DNS

While the other addons are not strictly required, all Kubernetes clusters should have [cluster DNS](#), as many examples rely on it.

Cluster DNS is a DNS server, in addition to the other DNS server(s) in your environment, which serves DNS records for Kubernetes services.

Containers started by Kubernetes automatically include this DNS server in their DNS searches.

Web UI (Dashboard)

[Dashboard](#) is a general purpose, web-based UI for Kubernetes clusters. It allows users to manage and troubleshoot applications running in the cluster, as well as the cluster itself.

Container Resource Monitoring

[Container Resource Monitoring](#) records generic time-series metrics about containers in a central database, and provides a UI for browsing that data.

Cluster-level Logging

A [cluster-level logging](#) mechanism is responsible for saving container logs to a central log store with search/browsing interface.

Network Plugins

[Network plugins](#) are software components that implement the container network interface (CNI) specification. They are responsible for allocating IP addresses to pods and enabling them to communicate with each other within the cluster.

What's next

Learn more about the following:

- [Nodes](#) and [their communication](#) with the control plane.
- Kubernetes [controllers](#).
- [kube-scheduler](#) which is the default scheduler for Kubernetes.
- Etcd's official [documentation](#).
- Several [container runtimes](#) in Kubernetes.
- Integrating with cloud providers using [cloud-controller-manager](#).
- [kubectl](#) commands.

Feedback

Was this page helpful?

☐ Yes ☐ No

Last modified May 19, 2023 at 2:06 PM PST: [Add CNI to list of addons \(a219b8c2b5\)](#)