

The Django logo, featuring the word "django" in a white, lowercase, sans-serif font.

The Web framework for perfectionists with deadlines.

May.04

Change a django password manually

Posted by **laur** in **Software**

The other day I've been confronted with a strange situation: I forgot the admin password for a [django](#) application. I was playing with installing my own pypi repository, I've configured and deployed a test application and, after a couple of weeks, I forgot the password. I tried several times but I knew that I used something silly and... unfortunate. Even worse, the user name I thought I used was not the one I had set up for the test. Oops 😊

After looking online for options I've found the following:

- Reinstall the app – This would be a pity because I already have some data loaded in
- Go to the DB and reset the password (would need to calculate a new hash = not nice)
- Use the command line

Preparation

Using the command line would make sense in this case, so here are the steps I followed:

1. Log in on your server's shell (e.g. ssh). If you don't have a shell, then you're out of luck.

```
ssh user@server.name
```

2. Activate the python environment you're using for your web app. It's likely that you use a **virtualenv**, so if you have bash:

```
1 $ source /_your/_virtenv/_path_/bin/activate
2
```

Of course, replace `/_your/_virtenv/_path_/` with the actual location of your virtual environment.

If you don't use virtualenv, replicate the setup steps you are performing when launching the application (setting up the PATH, environment variables etc.)

This will give you access to all python libraries, including django.

Use the shell, Luke!

1. Enter django shell:

```
1 cd /_your/_app/_path_/
2 python manage.py shell
3
```

Change `/_your/_app/_path_/` with the location where your application code is placed.

Now you should have a python shell prompt.

2. Import the `User` model:

```
1 from django.contrib.auth.models import User
2
```

3. Get the users:

```
1 users = User.objects.all()
```

If you don't have too many users, you may want to list them:

```
1 print users
2
```

4. Select the user desired:

```
1 user = users[0]
2
```

The first user is usually the admin user.

5. Set the new password:

```
1 user.set_password('_new_password_')
2
```

and save

```
1 user.save()
2
```

6. Log in in your app with the user name and the new password

Although it looks complicated, the python side is quite simple. We do the extra assignment (`user = users[0]`) because `User.objects.all()` is a lazy operation and it returns in fact a queryset.

HTH,

A little experiment: If you find this post and ad below useful, please check the ad out 😊

Submit a Comment

Your email address will not be published. Required fields are marked *

Comment

Name *

Email *

Website

POST COMMENT

☐ Notify me of follow-up comments by email.

☐ Notify me of new posts by email.

Tags

[android](#) [app](#) [application](#) [bootstrap](#) [C](#)

[cache](#) [change](#) [colour](#) [configuration](#) [cx_oracle](#) [data](#)

[db](#) [dbus](#) [django](#) [ergodox](#) [error](#) [google](#)

Categories

[EPSO](#)

[Gaming](#)

[Hardware](#)

Pages

[About me](#)

[Projects](#)

gradle house html insert **java** javascript

keyboard laptop large lg linux

management notification **old** oracle osx

outlook postgres project proxy

python qt sql studio test windows

xml xmfield

House

Idea

IT

Project Management

Random

Software

Tutorial

Uncategorized

Proudly powered by WordPress Theme: Serene by Elegant Themes.
