

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP
- PL/I
- PL/SQL
- Python**
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



## Python static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PYTHON code

All rules 216

Vulnerability 29

Bug 55

Security Hotspot 31

Code Smell 101

Tags

Search by name...



object



Variables, classes and functions should be defined before being used



Identity operators should not be used with dissimilar types



Only strings should be listed in "\_\_all\_\_"



"\_\_init\_\_" should not return a value



"yield" and "return" should not be used outside functions



String formatting should not lead to runtime errors



Recursion should not be infinite



Silly equality checks should not be made



Granting access to S3 buckets to all or authenticated users is security-sensitive



Hard-coded credentials are security-sensitive



Functions returns should not be invariant

### The "open" builtin function should be called with a valid mode

Analyze your code



The open builtin can open files in different modes, which are provided as a combination of characters. Using an invalid sequence of characters will at best make open fail, or worse, it will have an undefined behavior (ex: it might ignore some characters).

A valid mode:

- should contain one and only one of the following characters: "r" (read), "w" (write), "a" (append), "x" (create).
- should contain zero or one of the following characters: "t" (text), "b" (binary).
- should contain zero or one "+" character (open for updating)
- cannot contain "a", "w", "+", or "x" if "U" (universal newlines) is used. Note that "U" has no effect in python 3, it is deprecated and shouldn't be used anymore.

This rule raises an issue when an invalid "mode" is provided to the open builtin.

#### Noncompliant Code Example

```
# In python 3 the following fails
# In python 2.7.16 on MacOS, "open" will just ignore th
with open("test.txt", "aw") as f: # Noncompliant
    pass
```

#### Compliant Solution


```
with open("test.txt", "a") as f:
    pass
```

See


- [Python documentation - the open builtin](#)

Available In:


sonarlint | sonarcloud | sonarqube

 Code Smell


The "exec" statement should not be used

 Code Smell


Backticks should not be used

 Code Smell

Methods and field names should not differ only by capitalization

 Code Smell

JWT should be signed and verified

 Vulnerability