

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP**
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules 268

Vulnerability 40

Bug 51

Security Hotspot 33

Code Smell 144

Tags ▾

Search by name... 🔍

Code Smell
"switch case" clauses should not have too many lines of code
Code Smell
Assignments should not be made from within sub-expressions
Code Smell
Files should not have too many lines of code
Code Smell
Lines should not be too long
Code Smell
HTTP response headers should not be vulnerable to injection attacks
Vulnerability
"sleep" should not be called
Vulnerability
Static members should be referenced with "static::"
Bug
"require_once" and "include_once" should be used instead of "require" and "include"
Bug
Errors should not be silenced
Bug
Files should not contain characters before "<?php"
Bug
Method visibility should be explicitly declared
Bug

Unused assignments should be removed

Analyze your code

Code Smell

Major ?

cwe unused

A dead store happens when a local variable is assigned a value that is not read by any subsequent instruction. Calculating or retrieving a value only to then overwrite it or throw it away, could indicate a serious error in the code. Even if it's not an error, it is at best a waste of resources. Therefore all calculated values should be used.

Noncompliant Code Example

```
$i = $a + $b; // Noncompliant; calculation result not u
$i = compute();
```

Compliant Solution

```
$i = $a + $b;
$i += compute();
```

Exceptions

This rule ignores initializations to -1, 0, 1, null, true, false, "", [] and array().

See

- MITRE, CWE-563 - Assignment to Variable without Use ("Unused Variable")


Available In:

sonarlint


sonarcloud

sonarqube


Controlling permissions is security-sensitive

 Security Hotspot


Writing cookies is security-sensitive

 Security Hotspot

Framework-provided functions should be used to test exceptions

 Code Smell

Unicode-aware versions of character classes should be preferred

 Code Smell

Alias functions should not be used

 Code Smell