

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP**
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules 268

Vulnerability 40

Bug 51

Security Hotspot 33

Code Smell 144

Tags ▾

Search by name... 🔍

XML parsers should not be vulnerable to XXE attacks	Vulnerability
A secure password should be used when connecting to a database	Vulnerability
XPath expressions should not be vulnerable to injection attacks	Vulnerability
I/O function calls should not be vulnerable to path injection attacks	Vulnerability
LDAP queries should not be vulnerable to injection attacks	Vulnerability
OS commands should not be vulnerable to command injection attacks	Vulnerability
Class of caught exception should be defined	Bug
Caught Exceptions must derive from Throwable	Bug
Raised Exceptions must derive from Throwable	Bug
"\$this" should not be used in a static context	Bug
Hard-coded credentials are security-sensitive	Security Hotspot

Deserialization should not be vulnerable to injection attacks

Analyze your code attacks

Vulnerability

Blocker

injection cwe sans-top25 owasp

User-provided data such as URL parameters, POST data payloads or cookies should always be considered untrusted and tainted. Deserialization based on data supplied by the user could result in two types of attacks:

- Remote code execution attacks, where the structure of the serialized data is changed to modify the behavior of the object being unserialized.
- Parameter tampering attacks, where data is modified to escalate privileges or change for example quantity or price of products.

The best way to protect against deserialization attacks is probably to challenge the use of the deserialization mechanism in the application. They are cases were the use of deserialization mechanism was not justified and created breaches (CVE-2017-9785).

If the use of deserialization mechanisms is valid in your context, the problem could be mitigated in any of the following ways:

- Instead of using a native data interchange format, use a safe, standard format such as untyped JSON or structured data approaches such as Google Protocol Buffers.
- To ensure integrity is not compromised, add a digital signature (HMAC) to the serialized data that is validated before deserialization (this is only valid if the client doesn't need to modify the serialized data)
- As a last resort, restrict deserialization to be possible only to specific, whitelisted classes.

Noncompliant Code Example

```
$data = $_GET["data"];
$object = unserialize($data);
// ...
```


Compliant Solution

```
$data = $_GET["data"];


list($hash, $data) = explode('|', $data, 2);
$hash_confirm = hash_hmac("sha256", $data, "secret-key")

// Confirm that the data integrity is not compromised
if ($hash === $hash_confirm) {
    $object = unserialize($data);
    // ...
}
```


Test class names should end with "Test"

 Code Smell


Tests should include assertions

 Code Smell


TestCases should contain tests

 Code Smell

Variable variables should not be used

 Code Smell

A new session should be created during user authentication

 Vulnerability

See

- [OWASP Top 10 2021 Category A8](#) - Software and Data Integrity Failures
- [OWASP Top 10 2017 Category A8](#) - Insecure Deserialization
- [MITRE, CWE-20](#) - Improper Input Validation
- [MITRE, CWE-502](#) - Deserialization of Untrusted Data
- [SANS Top 25](#) - Risky Resource Management

Available In:

sonarcloud  | **sonarqube**  Developer Edition

© 2008-2022 SonarSource S.A., Switzerland. All content is copyright protected. SONAR, SONARSOURCE, SONARLINT, SONARQUBE and SONARCLOUD are trademarks of SonarSource S.A. All other trademarks and copyrights are the property of their respective owners. All rights are expressly reserved.
[Privacy Policy](#)