

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP**
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



# PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules 268

Vulnerability 40

Bug 51

Security Hotspot 33

Code Smell 144

Tags ▾

Search by name...

be used to end lines	
More than one property should not be declared per statement	
The "var" keyword should not be used	
"<?php" and "<?=" tags should be used	
File names should comply with a naming convention	
Comments should not be located at the end of lines of code	
Local variable and function parameter names should comply with a naming convention	
Field names should comply with a naming convention	
Lines should not end with trailing whitespaces	
Files should contain an empty newline at the end	
Modifiers should be declared in the correct order	
An open curly brace should be located at the beginning of a line	

Static members should be referenced with "static::"

Analyze your code

Bug

Minor

pitfall

References in a class to static class members (fields or methods) can be made using either `self::$var` or `static::$var` (introduced in 5.3). The difference between the two is one of scope. Confusingly, in subclasses, the use of `self::` references the original definition of the member, i.e. the superclass version, rather than any override at the subclass level. `static::`, on the other hand, references the class that was called at runtime.

Noncompliant Code Example

```
<?php

class Toy {

    public static function status() {
        self::getStatus(); // Noncompliant; will always print "Sticks are fun!"
    }

    protected static function getStatus() {
        echo "Sticks are fun!";
    }
}

class Ball extends Toy {

    protected static function getStatus() { // Doesn't actually print "Balls are fun!"
        echo "Balls are fun!";
    }
}

$myBall = new Ball();
$myBall::status(); // Prints "Sticks are fun!"
```

Compliant Solution

```
<?php

class Toy {

    public static function status() {
        static::getStatus(); // Compliant
    }

    protected static function getStatus() {
        echo "Sticks are fun!";
    }
}

class Ball extends Toy {

    protected static function getStatus() {
```

An open curly brace should be located at the end of a line

 Code Smell


Tabulation characters should not be used

 Code Smell

Method and function names should comply with a naming convention

 Code Smell

Creating cookies with broadly defined "domain" flags is security-sensitive

 Security Hotspot

```
        echo "Balls are fun!";
    }
}

$myBall = new Ball();
$myBall::status(); // Prints "Balls are fun!"
```

#### Exceptions

No issue is raised when `self` is used on a constant field, a private field or a private method.

```
class A
{
    private static $somevar = "hello";
    const CONSTANT = 42;

    private static function foo()
    {
        $var = self::$somevar . self::CONSTANT; // Should be OK
        self::foo(); // Should be OK
    }
}
```

Available In:

**sonarlint**  | **sonarcloud**  | **sonarqube** 