

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP**
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



# PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules 268

Vulnerability 40

Bug 51

Security Hotspot 33

Code Smell 144

Tags ▾

Search by name...

	Code Smell
	Classes named like "Exception" should extend "Exception" or a subclass
	Code Smell
	Two branches in a conditional structure should not have exactly the same implementation
	Code Smell
	Unused assignments should be removed
	Code Smell
	Method arguments with default values should be last
	Code Smell
	A reason should be provided when skipping a test
	Code Smell
	"__construct" functions should not make PHP 4-style calls to parent constructors
	Code Smell
	PHP 4 constructor declarations should not be used
	Code Smell
	Deprecated predefined variables should not be used
	Code Smell
	"switch" statements should not have too many "case" clauses
	Code Smell
	Classes should not have too many methods
	Code Smell
	Functions should not have too many lines of code
	Code Smell

## Unicode Grapheme Clusters should be avoided inside regex character classes

Analyze your code

Bug

Major

regex

When placing Unicode **Grapheme Clusters** (characters which require to be encoded in multiple **Code Points**) inside a character class of a regular expression, this will likely lead to unintended behavior.

For instance, the grapheme cluster `ö` requires two code points: one for `'c'`, followed by one for the *umlaut* modifier `'\u{0308}'`. If placed within a character class, such as `[ö]`, the regex will consider the character class being the enumeration `[c\u{0308}]` instead. It will, therefore, match every `'c'` and every *umlaut* that isn't expressed as a single codepoint, which is extremely unlikely to be the intended behavior.

This rule raises an issue every time Unicode Grapheme Clusters are used within a character class of a regular expression.

### Noncompliant Code Example

```
preg_replace("/[öä]/", "x", "cöä"); // Noncompliant, print
```

### Compliant Solution

```
preg_replace("/c|ä/", "x", "cöä"); // print "cXxä"
```

Available In:

sonarlint

sonarcloud

sonarqube

**"for" loop stop conditions should be invariant**

 Code Smell

**Sections of code should not be commented out**

 Code Smell

**Unused function parameters should be removed**

 Code Smell

**Unused "private" methods should be removed**

 Code Smell