

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules (268) Vulnerability (40) Bug (51) Security Hotspot (33) Code Smell (144)

Tags ▾

Search by name... 🔍

be used to end lines	Code Smell
More than one property should not be declared per statement	Code Smell
The "var" keyword should not be used	Code Smell
"<?php" and "<?=" tags should be used	Code Smell
File names should comply with a naming convention	Code Smell
Comments should not be located at the end of lines of code	Code Smell
Local variable and function parameter names should comply with a naming convention	Code Smell
Field names should comply with a naming convention	Code Smell
Lines should not end with trailing whitespaces	Code Smell
Files should contain an empty newline at the end	Code Smell
Modifiers should be declared in the correct order	Code Smell
An open curly brace should be located at the beginning of a line	Code Smell

Neither DES (Data Encryption Standard) nor DESede (3DES) should be used

Analyze your code

Vulnerability Blocker cwe owasp sans-top25

According to the US National Institute of Standards and Technology (NIST), the Data Encryption Standard (DES) is no longer considered secure:

Adopted in 1977 for federal agencies to use in protecting sensitive, unclassified information, the DES is being withdrawn because it no longer provides the security that is needed to protect federal government information.

Federal agencies are encouraged to use the Advanced Encryption Standard, a faster and stronger algorithm approved as FIPS 197 in 2001.

For similar reasons, RC2 should also be avoided.

Noncompliant Code Example

```
<?php
    $ciphertext = mcrypt_encrypt(MCRYPT_DES, $key, $plaintext
    // ...
    $ciphertext = mcrypt_encrypt(MCRYPT_DES_COMPAT, $key, $p
    // ...
    $ciphertext = mcrypt_encrypt(MCRYPT_TRIPLEDES, $key, $pl
    // ...
    $ciphertext = mcrypt_encrypt(MCRYPT_3DES, $key, $plainte

    $cipher = "des-ede3-cfb"; // Noncompliant
    $ciphertext_raw = openssl_encrypt($plaintext, $cipher, $
?>
```

Compliant Solution

```
<?php
    $ciphertext = mcrypt_encrypt(MCRYPT_RIJNDAEL_128, $key,
?>
```

See

- OWASP Top 10 2021 Category A2 - Cryptographic Failures
- OWASP Top 10 2017 Category A6 - Security Misconfiguration
- MITRE, CWE-326 - Inadequate Encryption Strength
- MITRE, CWE-327 - Use of a Broken or Risky Cryptographic Algorithm
- SANS Top 25 - Porous Defenses
- Derived from FindSecBugs rule [DES / DESede Unsafe](#)

Deprecated

This rule is deprecated; use {rule:php:S5547} instead.

Available In:

An open curly brace should be located at the end of a line

 Code Smell


Tabulation characters should not be used

 Code Smell

Method and function names should comply with a naming convention

 Code Smell

Creating cookies with broadly defined "domain" flags is security-sensitive

 Security Hotspot