

- Secrets
- ABAP
- Apex
- C
- C++
- CloudFormation
- COBOL
- C#
- CSS
- Flex
- Go
- HTML
- Java
- JavaScript
- Kotlin
- Objective C
- PHP**
- PL/I
- PL/SQL
- Python
- RPG
- Ruby
- Scala
- Swift
- Terraform
- Text
- TypeScript
- T-SQL
- VB.NET
- VB6
- XML



PHP static code analysis

Unique rules to find Bugs, Vulnerabilities, Security Hotspots, and Code Smells in your PHP code

All rules 268

Vulnerability 40

Bug 51

Security Hotspot 33

Code Smell 144

Tags ▾

Search by name...



be used to end lines

Code Smell

More than one property should not be declared per statement

Code Smell

The "var" keyword should not be used

Code Smell

"<?php" and "<?=" tags should be used

Code Smell

File names should comply with a naming convention

Code Smell

Comments should not be located at the end of lines of code

Code Smell

Local variable and function parameter names should comply with a naming convention

Code Smell

Field names should comply with a naming convention

Code Smell

Lines should not end with trailing whitespaces

Code Smell

Files should contain an empty newline at the end

Code Smell

Modifiers should be declared in the correct order

Code Smell

An open curly brace should be located at the beginning of a line

Test methods should be discoverable

Analyze your code

Code Smell Major tests unused phpunit

The PHPUnit test runner does execute public methods defined within test classes that have a name starting with "test" or the @test annotation. Methods that do not convey to this will not get executed.

This rule raises an issue on methods marked as test methods (by name or annotation) but do not have a public visibility. An issue is also raised on public methods that are not marked as tests, do contain assertions, and are not called from within another discoverable test method within the class. No issues are raised in abstract classes.

Noncompliant Code Example

```
class MyTest extends \PHPUnit\Framework\TestCase {
    private function testA() { // Noncompliant
        $this->assertTrue(getValue());
    }

    public function b() { // Noncompliant
        $this->assertTrue(getValue());
    }
}
```

Compliant Solution






```
class MyTest extends \PHPUnit\Framework\TestCase {
    public function testA() { // Compliant
        $this->assertTrue(getValue());
    }

    public function testB() {
        $this->b();
    }

    public function b() { // Compliant
        $this->assertTrue(getValue());
    }
}
```

Available In:

sonarlint sonarcloud sonarqube

 Code Smell
An open curly brace should be located at the end of a line  Code Smell
Tabulation characters should not be used  Code Smell
Method and function names should comply with a naming convention  Code Smell
Creating cookies with broadly defined "domain" flags is security-sensitive  Security Hotspot