

Introduction

Set up

Prepare the app

Deploy the app

View logs

Define a Procfile

Scale the app

Declare app dependencies

Run the app locally

Push local changes

Provision add-ons

Start a one-off dyno

Define config vars

Use a database

Next steps

Define a Procfile

A Procfile (<https://devcenter.heroku.com/articles/procfile>), is a text file in the root directory of your application, that explicitly declares what command should be executed to start your app.

To view the Procfile in the example app you deployed, type `type Procfile`. You will see that it looks like this: `web: puma -t 5:5 -p ${PORT:-3000} -e ${RACK_ENV:-development}`.

The Procfile declares a single process type, `web`, and the command needed to run it. The name `web` is important here. It declares that this process type will be attached to the HTTP routing stack (<https://devcenter.heroku.com/articles/http-routing>) of Heroku, and receive web traffic when deployed.

Procfiles can contain additional process types. For example, you might declare one for a background worker process that processes items off of a queue.

[Log in to report a problem \(/login?back_to=%2Farticles%2Fgetting-started-with-jruby%23define-a-procfile\)](/login?back_to=%2Farticles%2Fgetting-started-with-jruby%23define-a-procfile)

[I know what a Procfile is \(define-a-procfile\)](#)

(Log in (/login?back_to=%2Farticles%2Fgetting-started-with-jruby%23define-a-procfile) to save and track your progress)