How to Analyze and Tune MySQL Queries for Better Performance

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL cost-based optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

MySQL Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Cost-based Query Optimization

General idea

- Assign cost to operations
- Computes cost of partial or alternative plans
- Search for plan with lowest cost

- Cost-based optimizations:

Access method | Join order | Subquery strategy

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Input to Cost Model

- **IO-cost:**
  - Estimates from storage engine based on number of pages to read
  - Both index and data pages
- **Schema:**
  - Length of records and keys
  - Uniqueness for indexes
  - Nullability
- **Statistics:**
  - Number of rows in table
  - Key distribution/Cardinality:
    - Average number of records per key value
    - Only for indexed columns
    - Maintained by storage engine
  - Number of records in an index range

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Cost Model Example

SELECT SUM(o_totalprice) FROM orders
WHERE o_orderdate BETWEEN '1994-01-01' AND '1994-12-31';

Table scan:

- IO-cost: #pages in table
- CPU cost: #rows * ROW_EVALUATE_COST

Range scan (on secondary index):

- IO-cost: #pages to read from index + #rows_in_range
- CPU cost: #rows_in_range * ROW_EVALUATE_COST

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Cost Model

Example

EXPLAIN SELECT SUM(o_totalprice) FROM orders
WHERE o_orderdate BETWEEN '1994-01-01' AND '1994-12-31';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	ALL	i_o_orderdate	NULL	NULL	NULL	15000000	Using where

EXPLAIN SELECT SUM(o_totalprice) FROM orders
WHERE o_orderdate BETWEEN '1994-01-01' AND '1994-06-30';

Id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	range	i_o_orderdate	i_o_orderdate	4	NULL	2235118	Using index condition

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Cost Model Example: Optimizer Trace

join_optimization / row_estimation / table : orders / range_analysis

```
"table_scan": {
  "rows": 15000000,
  "cost": 3.12e6
} /* table_scan */,
"potential_range_indices": [
  {
    "index": "PRIMARY",
    "usable": false,
    "cause": "not_applicable“
  },
  {
    "index": "i_o_orderdate",
    "usable": true,
    "key_parts": [ "o_orderDATE", "o_orderkey" ]
  }
] /* potential_range_indices */,
...
```

```
"analyzing_range_alternatives": {
  "range_scan_alternatives": [
    {
      "index": "i_o_orderdate",
      "ranges": [ "1994-01-01 <= o_orderDATE <= 1994-12-31"
      ],
      "index_dives_for_eq_ranges": true,
      "rowid_ordered": false,
      "using_mrr": false,
      "index_only": false,
      "rows": 4489990,
      "cost": 5.39e6,
      "chosen": false,
      "cause": "cost"
    }
  ] /* range_scan_alternatives */,
  ...
} /* analyzing_range_alternatives */
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Cost Model vs Real World

Measured Execution Times

	Data in Memory	Data on Disk	Data on SSD
Table scan	6.8 seconds	36 seconds	15 seconds
Index scan	**5.2 seconds**	2.5 hours	30 minutes

Force Index Scan:

```
SELECT SUM(o_totalprice)
FROM orders FORCE INDEX (i_o_orderdate)
WHERE o_orderdate BETWEEN '1994-01-01' AND '1994-12-31';
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Performance Schema

Disk I/O

```
SELECT event_name, count_read, avg_timer_read/1000000000.0 “Avg Read Time (ms)”,
        sum_number_of_bytes_read  “Bytes Read”
  FROM performance_schema.file_summary_by_event_name
  WHERE event_name='wait/io/file/innodb/innodb_data_file';
```

Table Scan

event_name	count_read	Avg Read Time (ms)	Bytes Read
wait/io/file/innodb/innodb_data_file	115769	0.0342	1896759296

Index Scan

event_name	count_read	Avg Read Time (ms)	Bytes Read
wait/io/file/innodb/innodb_data_file	2188853	4.2094	35862167552

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Selecting Access Method

Finding the optimal method to read data from storage engine

- For each table, find the best access method:
  - Check if the access method is useful
  - Estimate cost of using access method
  - Select the cheapest to be used
- Choice of access method is cost based

Main access methods:

- Table scan
- Index scan
- Ref access
- Range scan
- Index merge
- Loose index scan

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Ref Access

Single Table Queries

EXPLAIN SELECT * FROM customer WHERE c_custkey = 570887;

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	customer	const	PRIMARY	PRIMARY	4	const	1	NULL

EXPLAIN SELECT * FROM orders WHERE o_orderdate = '1992-09-12';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	ref	i_o_orderdate	i_o_orderdate	4	const	6271	NULL

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Ref Access

Join Queries

EXPLAIN SELECT *
FROM orders JOIN customer ON c_custkey = o_custkey
WHERE o_orderdate = '1992-09-12';

Id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	ref	i_o_orderdate, i_o_custkey	i_o_orderdate	4	const	6271	Using where
1	SIMPLE	customer	eq_ref	PRIMARY	PRIMARY	4	dbt3.orders. o_custkey	1	NULL

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Ref Access

Join Queries, continued

EXPLAIN SELECT *
FROM orders JOIN customer ON c_custkey = o_custkey
WHERE c_acctbal < -1000;

Id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	customer	ALL	PRIMARY	NULL	NULL	NULL	1500000	Using where
1	SIMPLE	orders	ref	i_o_custkey	i_o_custkey	5	dbt3.customer. c_custkey	7	NULL

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer

- Goal: find the “minimal” ranges for each index that needs to be read
- Example:

  SELECT * FROM t1 WHERE (key1 > 10 AND key1 < 20) AND key2 > 30

- Range scan using INDEX(key1):

- Range scan using INDEX(key2):

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer

Optimizer Trace show ranges

```
SELECT a, b FROM t1
WHERE a > 10
    AND a < 25
    AND a NOT IN (11, 19))
    AND (b < 5 OR b > 10);
```

```
"analyzing_range_alternatives": {
  "range_scan_alternatives": [
    {
      "index": "i_a",
      "ranges": [
        "10 < a < 11",
        "11 < a < 19",
        "19 < a < 25"
      ],
      "index_dives_for_eq_ranges": true,
      "rowid_ordered": false,
      "using_mrr": false,
      "index_only": false,
      "rows": 3,
      "cost": 6.61,
      "chosen": true
    },
    {
      "index": "i_b",
      "ranges": [
        "NULL < b < 5",
        "10 < b"
      ],
      "index_dives_for_eq_ranges": true,
      "rowid_ordered": false,
      …
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer: Case Study

Why table scan?

SELECT * FROM orders
WHERE YEAR(o_orderdate) = 1997 AND MONTH(o_orderdate) = 5
AND o_clerk LIKE '%01866';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	ALL	NULL	NULL	NULL	NULL	15000000	Using where

Index not considered

```
mysql> SELECT * FROM orders WHERE year(o_orderdate) = 1997 AND MONTH(…
...
15 rows in set (8.91 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer: Case Study

Rewrite query to avoid functions on indexed columns

SELECT * FROM orders
WHERE o_orderdate BETWEEN '1997-05-01' AND '1997-05-31'
AND o_clerk LIKE '%01866';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	range	i_o_orderdate	i_o_orderdate	4	NULL	376352	Using index condition; Using where

```
mysql> SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' AND …
...
15 rows in set (0.91 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer: Case Study

Adding another index

CREATE INDEX i_o_clerk ON orders(o_clerk);

SELECT * FROM orders
WHERE o_orderdate BETWEEN '1997-05-01' AND '1997-05-31'
AND o_clerk LIKE '%01866';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	range	i_o_orderdate	i_o_orderdate	4	NULL	376352	Using index condition; Using where

New index not considered

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer: Case Study

Rewrite query, again

SELECT * FROM orders
WHERE o_orderdate BETWEEN '1997-05-01' AND '1997-05-31'
AND o_clerk = 'Clerk#000001866';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	range	i_o_orderdate, i_o_clerk	i_o_clerk	16	NULL	1504	Using index condition; Using where

```
mysql> SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' AND …
...
15 rows in set (0.01 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Access for Multi-part Index

Example table with multi-part index

- Table:

- INDEX idx(a, b, c);

- Logical storage layout of index:

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Range Optimizer: Case Study

Create multi-column index

CREATE INDEX i_o_clerk_date ON orders(o_clerk, o_orderdate);

SELECT * FROM orders
WHERE o_orderdate BETWEEN '1997-05-01' AND '1997-05-31'
AND o_clerk = 'Clerk#000001866';

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	range	i_o_orderdate, i_o_clerk, i_o_clerk_date	i_o_clerk_date	20	NULL	14	Using index condition

```
mysql> SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' AND …
...
15 rows in set (0.00 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Performance Schema: Query History

UPDATE performance_schema.setup_consumers
SET enabled='YES' WHERE name = 'events_statements_history';

```
mysql> SELECT sql_text, (timer_wait)/1000000000.0 “Time (ms)”, rows_examined FROM
  performance_schema.events_statements_history ORDER BY timer_start;
  +-----------------------------------------------------------------+--------+------+
  | sql_text                                                        | Time (ms) | rows_examined |
  +-----------------------------------------------------------------+--------+------+
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 8.1690 | 1505 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 7.2120 | 1505 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 8.1613 | 1505 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 7.0535 | 1505 |
  | CREATE INDEX i_o_clerk_date ON orders(o_clerk,o_orderdate) |82036.4190 |    0 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 0.7259 |   15 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 0.5791 |   15 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 0.5423 |   15 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 0.6031 |   15 |
  | SELECT * FROM orders WHERE o_orderdate BETWEEN '1997-05-01' … | 0.2710 |   15 |
  +-----------------------------------------------------------------+--------+------+
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Join Optimizer

”Greedy search strategy”

- Goal: Given a JOIN of N tables, find the best JOIN ordering
- Strategy:
  - Start with all 1-table plans
  - Expand each plan with remaining tables
    - Depth-first
  - If “cost of partial plan” > “cost of best plan”:
    - “prune” plan
  - Heuristic pruning:
    - Prune less promising partial plans
    - May in rare cases miss most optimal plan (turn off with **set optimizer_prune_level = 0**)

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Complexity and Cost of Join Optimizer

Join of N tables: *N!* possible plans to evaluate

Heuristics to reduce the number of plans to evaluate:

- Use **optimizer_search_depth** to limit the number of tables to consider
- Pre-sort tables on *size* and *key dependency* order (Improved in MySQL 5.6)
- When adding the next table to a partial plan, add all tables that it has an equality reference to (New in MySQL 5.6)

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Join Optimizer: Case study

DBT-3 Query 8: National Market Share Query

```
SELECT o_year, SUM(CASE WHEN nation = 'FRANCE' THEN volume ELSE 0 END)  / SUM(volume) AS
        mkt_share
FROM (
        SELECT EXTRACT(YEAR FROM o_orderdate) AS o_year,
                l_extendedprice * (1 - l_discount) AS volume, n2.n_name AS nation
        FROM part
          JOIN lineitem ON p_partkey = l_partkey
          JOIN supplier ON s_suppkey = l_suppkey
          JOIN orders ON l_orderkey = o_orderkey
          JOIN customer ON o_custkey = c_custkey
          JOIN nation n1 ON c_nationkey = n1.n_nationkey
          JOIN region ON  n1.n_regionkey = r_regionkey
          JOIN nation n2 ON s_nationkey = n2.n_nationkey
        WHERE r_name = 'EUROPE' AND o_orderdate BETWEEN '1995-01-01' AND '1996-12-31'
            AND p_type = 'PROMO BRUSHED STEEL'
) AS all_nations GROUP BY o_year ORDER BY o_year;
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Join Optimizer: Case Study

MySQL Workbench: Visual EXPLAIN

Execution time: 3 min. 28 sec.

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Join Optimizer: Case study

Force early processing of high selectivity predicates

```
SELECT o_year, SUM(CASE WHEN nation = 'FRANCE' THEN volume ELSE 0 END)  / SUM(volume) AS
        mkt_share
FROM (
        SELECT EXTRACT(YEAR FROM o_orderdate) AS o_year,
            l_extendedprice * (1 - l_discount) AS volume, n2.n_name AS nation
        FROM part
          STRAIGHT_JOIN lineitem ON p_partkey = l_partkey
          JOIN supplier ON s_suppkey = l_suppkey
          JOIN orders ON l_orderkey = o_orderkey
          JOIN customer ON o_custkey = c_custkey
          JOIN nation n1 ON c_nationkey = n1.n_nationkey
          JOIN region ON  n1.n_regionkey = r_regionkey
          JOIN nation n2 ON s_nationkey = n2.n_nationkey
        WHERE r_name = 'EUROPE' AND o_orderdate BETWEEN '1995-01-01' AND '1996-12-31'
            AND p_type = 'PROMO BRUSHED STEEL'
 ) AS all_nations GROUP BY o_year ORDER BY o_year;
```

part before lineitem

Highest selectivity

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Join Optimizer: Case study

Improved join order

Execution time: 7 seconds

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

MySQL 5.7: Cost Information in Structured EXPLAIN

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

ORDER BY Optimizations

- General solution; “Filesort”:
  - Store query result in temporary table before sorting
  - If data volume is large, may need to sort in several passes with intermediate storage on disk.
- Optimizations:
  - Take advantage of index to generate query result in sorted order
  - For ”LIMIT *n*” queries, maintain priority queue of *n* top items in memory instead of filesort. (New in MySQL 5.6)

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort

SELECT * FROM orders ORDER BY o_totalprice ;

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	orders	ALL	NULL	NULL	NULL	NULL	15000000	Using filesort

SELECT c_name, o_orderkey, o_totalprice
FROM orders JOIN customer ON c_custkey = o_custkey
WHERE c_acctbal < -1000 ORDER BY o_totalprice ;

id	select type	table	type	possible keys	key	key len	ref	rows	extra
1	SIMPLE	customer	ALL	PRIMARY	NULL	NULL	NULL	1500000	Using where; Using temporary; Using filesort
1	SIMPLE	orders	ref	i_o_custkey	i_o_custkey	5	...	7	NULL

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort

Status variables

Status variables related to sorting:

```
mysql> show status like 'Sort%';
+-------------------+--------+
| Variable_name     | Value  |
+-------------------+--------+
| Sort_merge_passes | 1      |
| Sort_range        | 0      |
| Sort_rows         | 136170 |
| Sort_scan         | 1      |
+-------------------+--------+
```

>0: Intermediate storage on disk.
Consider increasing `sort_buffer_size`

Number of sort operations
(range scan or table/index scans)

Number of rows sorted

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort: Case Study

```
mysql> FLUSH STATUS;

Query OK, 0 rows affected (0.00 sec)

mysql> SELECT AVG(o_totalprice) FROM
  ( SELECT * FROM orders
    ORDER BY o_totalprice DESC
    LIMIT 100000) td;
+--------------------+
| AVG(o_totalprice)  |
+--------------------+
| 398185.986158      |
+--------------------+
1 row in set (24.65 sec)
```

Unnecessary large data volume!

```
mysql> SHOW STATUS LIKE 'sort%';
+--------------------+--------+
| Variable_name      | Value  |
+--------------------+--------+
| Sort_merge_passes  |   1432 |
| Sort_range         |      0 |
| Sort_rows          | 100000 |
| Sort_scan          |      1 |
+--------------------+--------+
4 rows in set (0.00 sec)
```

Many intermediate sorting steps!

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort: Case Study

Reduce amount of data to be sorted

```
mysql> FLUSH STATUS;

Query OK, 0 rows affected (0.00 sec)

mysql> SELECT AVG(o_totalprice) FROM
  ( SELECT o_totalprice FROM orders
    ORDER BY o_totalprice DESC
    LIMIT 100000) td;
+--------------------+
| AVG(o_totalprice) |
+--------------------+
| 398185.986158      |
+--------------------+
1 row in set (8.18 sec)
```

```
mysql> SHOW STATUS LIKE 'sort%';
+--------------------+--------+
| Variable_name      | Value  |
+--------------------+--------+
| Sort_merge_passes  |    229 |
| Sort_range         |      0 |
| Sort_rows          | 100000 |
| Sort_scan          |      1 |
+--------------------+--------+
4 rows in set (0.00 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort: Case Study

Increase sort buffer (1 MB)

Default is 256 kB

```
mysql> set sort_buffer_size=1024*1024;

mysql> FLUSH STATUS;

Query OK, 0 rows affected (0.00 sec)

mysql> SELECT AVG(o_totalprice) FROM
  ( SELECT o_totalprice FROM orders
    ORDER BY o_totalprice DESC
    LIMIT 100000) td;
+-------------------+
| AVG(o_totalprice) |
+-------------------+
| 398185.986158     |
+-------------------+

1 row in set (7.24 sec)
```

```
mysql> SHOW STATUS LIKE 'sort%';
+-------------------+--------+
| Variable_name     | Value  |
+-------------------+--------+
| Sort_merge_passes |     57 |
| Sort_range        |      0 |
| Sort_rows         | 100000 |
| Sort_scan         |      1 |
+-------------------+--------+
4 rows in set (0.00 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Filesort: Case Study

Increase sort buffer even more (8 MB)

```
mysql> set
  sort_buffer_size=8*1024*1024;

mysql> FLUSH STATUS;

Query OK, 0 rows affected (0.00 sec)

mysql> SELECT AVG(o_totalprice) FROM
  ( SELECT o_totalprice FROM orders
    ORDER BY o_totalprice DESC
    LIMIT 100000) td;
+--------------------+
| AVG(o_totalprice)  |
+--------------------+
| 398185.986158      |
+--------------------+
1 row in set (6.30 sec)
```

```
mysql> SHOW STATUS LIKE 'sort%';
+--------------------+--------+
| Variable_name      | Value  |
+--------------------+--------+
| Sort_merge_passes  |      0 |
| Sort_range         |      0 |
| Sort_rows          | 100000 |
| Sort_scan          |      1 |
+--------------------+--------+
4 rows in set (0.00 sec)
```

NB! Bigger sort buffer than needed will give unnecessary overhead

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Use Index to Avoid Sorting

CREATE INDEX i_o_totalprice ON orders(o_totalprice);

SELECT AVG(o_totalprice) FROM
(SELECT o_totalprice FROM orders ORDER BY o_totalprice DESC LIMIT 100000) td;

id	select type	table	Type	possible keys	key	key len	ref	rows	extra
1	PRIMARY	<derived2>	ALL	NULL	NULL	NULL	NULL	100000	NULL
2	DERIVED	orders	index	NULL	i_o_totalprice	6	NULL	15000000	Using index

```
mysql> SELECT AVG(o_totalprice) FROM (
   SELECT o_totalprice FROM orders
   ORDER BY o_totalprice DESC LIMIT 100000) td;
...
1 row in set (0.06 sec)
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Useful tools

- MySQL Enterprise Monitor (MEM), Query Analyzer
  - Commercial product
- Performance schema, MySQL sys schema
- EXPLAIN
- EXPLAIN FORMAT=JSON
- Optimizer trace
- Slow log
- Status variables (SHOW STATUS LIKE ’Handler%’)

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

MySQL Enterprise Monitor, Query Analyzer

ORACLE MySQL Enterprise Monitor

1 2 0 0 1 admin

Dashboards Events Query Analyzer Reports & Graphs Configuration Refresh: Every Minute

Browse Queries

Show / hide columns

Show 25 entries Export data options...

Showing 1 to 25 of 1,197 entries First Previous 1 2 3 4 5 Next Last

Query	Database		Counts			QRTi	Latency (hh:mm:ss.ms)					Rows	
			Exec	Err	Warn		Total	Max	Avg	Locks	Avg History	Total	Examined
COMMIT (1)	mem		24,707	0	0	0.92	20:27.872	5.828	0.050	0.000		0	0
INSERT INTO `mem__quan`...o` ) , `hostTo`) , ... (1)	mem		6,903	0	0	0.79	18:16.538	17.784	0.159	6.699		7,356	0
INSERT INTO `mem__quan`...on` = IF (VALUES (... (1)	mem		6,985	0	0	0.86	10:54.856	8.940	0.094	8.301		7,332	0
INSERT INTO `mem__quan`...en` ) ) , `lastSeen`) (1)	mem		7,025	37	0	1.00	3:11.791	11.220	0.027	4.436		13,947	0
INSERT INTO `mem__instr...tency`) , `latency`) (1)	mem		740	0	0	0.77	1:48.459	8.745	0.147	0.147		1,386	0
SELECT `mysqlconne0_` ....asProc18_1191_0_` , ... (1)	mem		974	0	0	0.90	1:01.829	12.359	0.063	0.353		974	974
SELECT `mysqlserve0_` ...._` . `hostCache` AS ... (1)	mem		1,801	0	0	0.93	53.661	13.351	0.030	0.636		1,801	1,801
INSERT INTO `mem__instr...es`) , `diskWrites`) (1)	mem		26	0	0	0.79	44.838	14.954	1.725	0.070		26	0
UPDATE `mem__inventory`...n` = ? WHERE `hid` = ? (1)	mem		321	0	0	0.80	43.886	9.668	0.137	0.044		321	321
UPDATE `mem__config` . ... ? WHERE `user_id` = ? (1)	mem		321	0	0	0.71	40.788	10.607	0.127	0.038		321	321
CREATE TEMPORARY TABLE ...(`id` INT8 NOT NULL) (1)	mem		13	0	0	0.14	36.525	12.055	2.810	0.000		0	0
INSERT INTO `mem__instr...nedTableDefinitions`) (1)	mem		26	0	0	0.64	34.348	13.349	1.321	0.003		27	0
UPDATE `mem__inventory`...p` = ? WHERE `hid` = ? (1)	mem		416	0	0	0.81	33.469	13.060	0.080	0.042		416	416
INSERT INTO `mem__instr...hed`) , `notCached`) (1)	mem		26	0	0	0.61	32.509	11.782	1.250	0.003		27	0
SELECT * FROM (SELECT ...m_no_index_used` AS ... (1)	mem		14	0	0	0.00	29.832	9.602	2.131	0.008		7,459	227,050
INSERT INTO `mem__instr...s`) , `connections`) (1)	mem		25	0	0	0.82	29.462	14.294	1.178	0.005		26	0
INSERT INTO `mem__instr... ( `sent` ) , `sent`) (1)	mem		25	0	0	0.82	28.991	14.332	1.160	0.003		26	0
SELECT `agent0_` . `hid.... `hid` = ? FOR UPDATE (1)	mem		909	0	0	0.96	28.632	6.964	0.031	0.158		909	909
UPDATE `mem__events` . ...me` = ? WHERE `id` = ? (1)	mem		395	0	0	0.92	27.544	10.061	0.070	0.038		395	395

Copyright © 2005, 2013, Oracle and/or its affiliates. All rights reserved.

3.0.1.7150 - Cerberus.local (192.168.1.67) - Sep 16, 2013 11:50:28 am (Up Since: 38 minutes ago) - About

ORACLE

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Query Analyzer Query Details

Canonical Query | **Example Query** | Explain Query | Graphs

The query with the longest execution time during the Time Span (usually the slowest but not always).

Sampled Query

truncated | full | formatted

```
SELECT
    mysqlserve0_.hid AS hid1124_0_, mysqlserve0_.`id` AS id2_1124_0_,
    mysqlserve0_.`lastContact` AS lastCont3_1124_0_,
    mysqlserve0_.`hasLastContact` AS hasLastC4_1124_0_,
    mysqlserve0_.`startTime` AS startTime5_1124_0_,
    mysqlserve0_.`hasStartTime` AS hasStart6_1124_0_,
    mysqlserve0_.`timestamp` AS timestamp7_1124_0_,
    mysqlserve0_.`capabilities` AS capabili8_1124_0_,
    mysqlserve0_.`hasCapabilities` AS hasCapab9_1124_0_,
    mysqlserve0_.`characterSet` AS charact10_1124_0_,
    mysqlserve0_.`hasCharacterSet` AS hasChar11_1124_0_,
    mysqlserve0_.`collation` AS collation12_1124_0_,
    mysqlserve0_.`hasCollation` AS hasColli3_1124_0_,
    mysqlserve0_.`connection` AS connection14_1124_0_,
    mysqlserve0_.`hasConnection` AS hasConn15_1124_0_,
    mysqlserve0_.`environment` AS environ16_1124_0_,
```

Execution Time
27,084 ms

Date
Sep 16, 2013 1:07:17 PM

User
service_manager

Thread ID
10,712

From Host
localhost

To Host

Source Location
None found.

Comments
None found.

Canonical Query | Example Query | Explain Query | **Graphs**

Graphs of a query during the Time Span

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Performance Schema

Some useful tables

- **events_statements_history**
  events_statements_history_long
  - Most recent statements executed
- **events_statements_summary_by_digest**
  - Summary for similar statements (same statement digest)
- **file_summary_by_event_name**
  - Interesting event: wait/io/file/innodb/innodb_data_file
- **table_io_waits_summary_by_table**
  table_io_waits_summary_by_index_usage
  - Statistics on storage engine access per table and index

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Performance Schema

Statement digest

- Normalization of queries to group statements that are similar to be grouped and summarized:

  SELECT * FROM orders WHERE o_custkey=10 AND o_totalprice>20
  SELECT * FROM orders WHERE o_custkey = 20 AND o_totalprice > 100

  ➡ **SELECT * FROM orders WHERE o_custkey = ? AND o_totalprice > ?**

- **`events_statements_summary_by_digest`**

  DIGEST, DIGEST_TEXT, COUNT_STAR, SUM_TIMER_WAIT, MIN_TIMER_WAIT, AVG_TIMER_WAIT, MAX_TIMER_WAIT, SUM_LOCK_TIME, SUM_ERRORS, SUM_WARNINGS, SUM_ROWS_AFFECTED, SUM_ROWS_SENT, SUM_ROWS_EXAMINED, SUM_CREATED_TMP_DISK_TABLES, SUM_CREATED_TMP_TABLES, SUM_SELECT_FULL_JOIN, SUM_SELECT_FULL_RANGE_JOIN, SUM_SELECT_RANGE, SUM_SELECT_RANGE_CHECK, SUM_SELECT_SCAN, SUM_SORT_MERGE_PASSES, SUM_SORT_RANGE, SUM_SORT_ROWS, SUM_SORT_SCAN, SUM_NO_INDEX_USED, SUM_NO_GOOD_INDEX_USED, FIRST_SEEN, LAST_SEEN

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Performance Schema

Statement events

- Tables:
  `events_statements_current` (Current statement for each thread)
  `events_statements_history` (10 most recent statements per thread)
  `events_statements_history_long` (10000 most recent statements)
- Columns:

  THREAD_ID, EVENT_ID, END_EVENT_ID, EVENT_NAME, SOURCE, TIMER_START, TIMER_END, TIMER_WAIT, LOCK_TIME, SQL_TEXT, DIGEST, DIGEST_TEXT, CURRENT_SCHEMA, OBJECT_TYPE, OBJECT_SCHEMA, OBJECT_NAME, OBJECT_INSTANCE_BEGIN, MYSQL_ERRNO, RETURNED_SQLSTATE, MESSAGE_TEXT, ERRORS, WARNINGS, ROWS_AFFECTED, ROWS_SENT, ROWS_EXAMINED, CREATED_TMP_DISK_TABLES, CREATED_TMP_TABLES, SELECT_FULL_JOIN, SELECT_FULL_RANGE_JOIN, SELECT_RANGE, SELECT_RANGE_CHECK, SELECT_SCAN, SORT_MERGE_PASSES, SORT_RANGE, SORT_ROWS, SORT_SCAN, NO_INDEX_USED, NO_GOOD_INDEX_USED, NESTING_EVENT_ID, NESTING_EVENT_TYPE

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

MySQL sys Schema / ps_helper

- Started as a collection of views, procedures and functions, designed to make reading raw Performance Schema data easier
- Implements many common DBA and Developer use cases
- Now bundled within MySQL Workbench
- Available on GitHub
  - https://github.com/MarkLeith/mysql-sys
- Examples of very useful functions:
  - format_time() , format_bytes(), format_statement()

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

MySQL sys Schema

Example

statement_analysis: Lists a normalized statement view with aggregated statistics, mimics the MySQL Enterprise Monitor Query Analysis view, ordered by the total execution time per normalized statement

```
mysql> select * from statement_analysis limit 1\G
*************************** 1. row ***************************
query: INSERT INTO `mem__quan` . `nor ... nDuration` = IF ( VALUES ( ...
db: mem
full_scan:
exec_count: 1110067
err_count: 0
warn_count: 0
total_latency: 1.93h
max_latency: 5.03 s
avg_latency: 6.27 ms
lock_latency: 00:18:29.18
rows_sent: 0
rows_sent_avg: 0
rows_examined: 0
rows_examined_avg: 0
tmp_tables: 0
tmp_disk_tables: 0
rows_sorted: 0
sort_merge_passes: 0
digest: d48316a218e95b1b8b72db5e6b177788!
first_seen: 2014-05-20 10:42:17
```

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Optimizer Trace: Query Plan Debugging

- EXPLAIN shows the selected plan
- TRACE shows WHY the plan was selected:
  - Alternative plans
  - Estimated costs
  - Decisions made
- JSON format

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Optimizer Trace: Example

```
SET optimizer_trace= “enabled=on“, end_markers_in_json=on;
SELECT * FROM t1, t2 WHERE f1=1 AND f1=f2 AND f2>0;
SELECT trace INTO DUMPFILE <filename>
    FROM information_schema.optimizer_trace;
SET optimizer_trace="enabled=off";
```

QUERY	SELECT * FROM t1,t2 WHERE f1=1 AND f1=f2 AND f2>0;
TRACE	“steps”: [{ "join_preparation": { "select#": 1,… } … } …]
MISSING_BYTES_BEYOND_MAX_MEM_SIZE	0
INSUFFICIENT_PRIVILEGES	0

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Program Agenda

1. Introduction to MySQL optimizer
2. Selecting data access method
3. Join optimizer
4. Sorting
5. Tools for monitoring, analyzing, and tuning queries
6. Influencing the Optimizer

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Influencing the Optimizer

When the optimizer does not do what you want

- Add indexes
- Force use of specific indexes:
  - USE INDEX, FORCE INDEX, IGNORE INDEX
- Force specific join order:
  - STRAIGHT_JOIN
- Adjust session variables
  - optimizer_switch flags: set optimizer_switch="index_merge=off"
  - Buffer sizes: set sort_buffer=8*1024*1024;
  - Other variables: set optimizer_prune_level = 0;

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

More information

- My blog:
  - http://oysteing.blogspot.com/
- Optimizer team blog:
  - http://mysqloptimizerteam.blogspot.com/
- MySQL Server Team blog
  - http://mysqlserverteam.com/
- MySQL forums:
  - Optimizer & Parser: http://forums.mysql.com/list.php?115
  - Performance: http://forums.mysql.com/list.php?24

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Safe Harbor Statement

The preceding is intended to outline our general product direction. It is intended for information purposes only, and may not be incorporated into any contract. It is not a commitment to deliver any material, code, or functionality, and should not be relied upon in making purchasing decisions. The development, release, and timing of any features or functionality described for Oracle's products remains at the sole discretion of Oracle.

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.

Q&A

Copyright © 2015, Oracle and/or its affiliates. All rights reserved.