

10.5.2 MySQLCursor.callproc() Method

Syntax:

```
result_args = cursor.callproc(proc_name, args=())
```

This method calls the stored procedure named by the `proc_name` argument. The `args` sequence of parameters must contain one entry for each argument that the procedure expects. `callproc()` returns a modified copy of the input sequence. Input parameters are left untouched. Output and input/output parameters may be replaced with new values.

Result sets produced by the stored procedure are automatically fetched and stored as `MySQLCursorBuffered` instances. For more information about using these result sets, see [stored_results\(\)](#).

Suppose that a stored procedure takes two parameters, multiplies the values, and returns the product:

```
CREATE PROCEDURE multiply(IN pFac1 INT, IN pFac2 INT, OUT pProd INT)
BEGIN
    SET pProd := pFac1 * pFac2;
END;
```

The following example shows how to execute the `multiply()` procedure:

```
>>> args = (5, 6, 0) # 0 is to hold value of the OUT parameter pProd
>>> cursor.callproc('multiply', args)
('5', '6', 30L)
```

Connector/Python 1.2.1 and up permits parameter types to be specified. To do this, specify a parameter as a two-item tuple consisting of the parameter value and type. Suppose that a procedure `sp1()` has this definition:

```
CREATE PROCEDURE sp1(IN pStr1 VARCHAR(20), IN pStr2 VARCHAR(20),
                    OUT pConCat VARCHAR(100))
BEGIN
    SET pConCat := CONCAT(pStr1, pStr2);
END;
```

To execute this procedure from Connector/Python, specifying a type for the `OUT` parameter, do this:

```
args = ('ham', 'eggs', (0, 'CHAR'))
result_args = cursor.callproc('sp1', args)
print(result_args[2])
```

