

# Mysql2 - A modern, simple and very fast Mysql library for Ruby - binding to libmysql

The Mysql2 gem is meant to serve the extremely common use-case of connecting, querying and iterating on results. Some database libraries out there serve as direct 1:1 mappings of the already complex C API's available. This one is not.

It also forces the use of UTF-8 [or binary] for the connection [and all strings in 1.9, unless `Encoding.default_internal` is set then it'll convert from UTF-8 to that encoding] and uses encoding-aware MySQL API calls where it can.

The API consists of two classes:

`Mysql2::Client` - your connection to the database

`Mysql2::Result` - returned from issuing a `#query` on the connection. It includes `Enumerable`.

## Installing

---

```
gem install mysql2
```

You may have to specify `--with-mysql-config=/some/random/path/bin/mysql_config`

## Usage

---

Connect to a database:

```
# this takes a hash of options, almost all of which map directly
# to the familiar database.yml in rails
# See
http://api.rubyonrails.org/classes/ActiveRecord/ConnectionAdapters/MysqlAdapter.html
client = Mysql2::Client.new(:host => "localhost", :username => "root")
```

Then query it:

```
results = client.query("SELECT * FROM users WHERE group='githubbers'")
```

Need to escape something first?

```
escaped = client.escape("gi'thu\"bbe\0r's")
results = client.query("SELECT * FROM users WHERE group='#{escaped}'")
```

You can get a count of your results with `results.count`.

Finally, iterate over the results:

```
results.each do |row|
  # conveniently, row is a hash
  # the keys are the fields, as you'd expect
  # the values are pre-built ruby primitives mapped from their corresponding
  # field types in MySQL
  # Here's an otter:
  http://farm1.static.flickr.com/130/398077070_b8795d0ef3_b.jpg
end
```

Or, you might just keep it simple:

```
client.query("SELECT * FROM users WHERE group='githubbers'").each do |row|
  # do something with row, it's ready to rock
end
```

How about with symbolized keys?

```
# NOTE: the :symbolize_keys and future options will likely move to the #query
# method soon
client.query("SELECT * FROM users WHERE
group='githubbers'").each(:symbolize_keys => true) do |row|
  # do something with row, it's ready to rock
end
```

You can get the headers and the columns in the order that they were returned by the query like this:

```
headers = results.fields # <= that's an array of field names, in order
results.each(:as => :array) do |row|
  # Each row is an array, ordered the same as the query results
  # An otter's den is called a "holt" or "couch"
end
```

## Cascading config

---

The default config hash is at:

[Mysql2::Client.default\\_query\\_options](#)

which defaults to:

```
{:async => false, :as => :hash, :symbolize_keys => false}
```